

# 20X2Characters Double Line VFD Customer Display

(Model No.:VFD220C)

## Features:

- 1 Doublelines 20\*2 characters VFD display;
- 1 Support26 countries languages;
- 1 Poleheight is adjustable;
- 1 360degree rotation angle;
- 1 SupportsESC/POS and CD5220 command
- 1 3kinds of different height for you choose

## Specifications:

- 1 Highbrightness Vacuum Fluorescent Display for excellent visibility over a wideviewing angle.
- 1 Availablein 9mm high characters.
- 1 40characters in 20 columns by 2 lines format.
- 1 Thirteensets of international characters, plus one set of user defined charactersallows total flexibility in display fonts.
- 1 Easyprogramming using Escape sequence commands.
- 1 Emulationof Aedex, Epson and DSP800 command sets.
- 1 Displaycan swivel and tilt to a wide range of angles.
- 1 Adjustabledisplay height.
- 1 Powermay be sourced from system, with the bracket and cable kit supplied in typicalconfiguration.
- 1 ACadaptors in various configurations for all AC voltages.

<b>Frame color</b>	Black / white/Cyan
<b>Display Color</b>	Blue-Green
<b>Display Method</b>	Vacuum Fluorescent Display
<b>Display Mode</b>	2lines*20characters
<b>Brightness</b>	700cd/m <sup>2</sup>
<b>Character type</b>	96 alphanumeric,26Kinds of international character set
<b>Character font</b>	5X7 Dot matrix
<b>Character size</b>	6.75mm x 3.75mm
<b>Dot Size</b>	0.8 x 0.55 mm
<b>Code page</b>	20 <b>Code page</b>
<b>Viewing Area</b>	-5~60°
<b>Panel Dimension</b>	204(W)*67(H)*40(D)
<b>Viewing Angle</b>	188mm(L)×40mm□W□
<b>Horizontal Rotation</b>	Max 350°
<b>Weight</b>	0.9KG
<b>Commands Mode</b>	ESC/POS/CD5220/DSP800/UTC.....

<b>Language Support</b>	US English, UK English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish...
<b>Interface</b>	RS232 (serial) or USB
<b>Baudrate</b>	2400/9600 BPS,
<b>MTBF</b>	40,000 hours
<b>Power supply</b>	DC5V 1A
<b>Certificate</b>	CE,ROHS,FCC



# VFD220C



[www.ocominc.com](http://www.ocominc.com)

