

Model	POS-G156W/A	
Name	15.6 inch all in one touch screen pos terminal	
Housing	plastic with metal combined	
Color	whole pearl white machine body or pearl white match gray machine body	
Main screen	15.6 inch touch screen monitor	
Resolution	1366*768	
Brightness	250cd/m ²	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.6inch display and 13.3 inch display W/ or W/o touch function, resolution 1366*768 for option	
Customer display	2*20 VFD mounted to back cover for option	
Performance		
Windows	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 th generation CPU for option
	System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for option
	Storage device	Msata SSD 64GB or higer, up to 256GB
	Audio	On board Real Tek ALC662 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
	Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Android	Motherboard	Rockchip series quad core RK3568 default , RK3288,RK3399 for option
	System Memory	On board DDRIV 2GB,4GB for option
	Storage device	on board16GB EMMC,32GB for option
	LAN	RJ45 port support 10/100Mbs internet
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Operating System	Android 7.1,up to Android 8.1 Android 11
Connectivity		
Windows and Android(J1900&RK3568)	power button*1	
	12V DC in jack*1	
	COM(RS232) * 1	
	LAN:RJ-45*1	
	USB *5	
	MIC in*1 , Audio out*1	
Windows (J1900)	LPT *1	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 (optional)	
	PS/2 *1 for mouse and keyboard	
Android (RK3568)	on board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TFcard slot*1,SIM slot*1	
Options		

80mm thermal printer	direct thermal printing
	150mm/s printing speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with auto cutter function and thermal head life 100km
	USB communication
58mm thermal printer	direct thermal printing
	80mm/s printing speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
	LPT communication
MSR	optional side MSR just for 15.6inch
Web camera	web camera mounted on top of the display for option
Speaker	80hm/5W speaker inside for option
Package	
Weight	Net 6.5Kg, Gross 8.5Kg for 15.6 dual screen
Package with foam inside	300*465*500mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%
Accessories	
Power adapter	110-240V/50-60HZ AC power input ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A output adaptor only for W/80mm printer machine
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside for option
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC





