

Scanner 16bit Auto Sense di codici a barre palmare con il basamento

(M / N: OCBs-LA04)

caratteristica:

- 1.Auto-induzione integrato, progettazione verde;
2. Alta velocità di scansione e lunga distanza di lettura;
- capacità di decodifica 3.Excellent;
- 4.KBW, RS232 e USB supportati;
- costruzione 5.Durable combinato con il futuro-impermeabilizzazione;

SPECIFICA:

Caratteristiche di performance	
Fonte di luce:	laser visibile (650-670nm)
Velocità di scansione:	100 scansioni al secondo
lettura Distanza	2.5 ~ 600 millimetri (100% UPC / EAN)
Tipo di scanner:	Bidirezionale
Risoluzione:	0,10 millimetri (4mil) a PCS 0.9
Contrasto di stampa minima:	20%, minima differenza riflettente (@ 650nm)
Capacità di decodifica:	UPC / EAN, UPC / EAN con supplementi, UCC / EAN128, il codice 39, il codice 39 ASCII completa, codice 39 Trioptic, codice 128, codice 128 ASCII completa, Codabar, Interleaved 2 of 5, discreta 2 su 5, codice 93, MSI , il codice 11, ATA, varianti RSS, cinese 2 di 5 ...
Caratteristiche fisiche	
Interfacce supportate:	PS2, RS232, USB
voltaggio:	DC + 5V +/- 5%
Attuale:	100 mA
Idle corrente:	& Amp; Lt;40 mA
Fonte di potere:	Host potere o esterna (RS232) Alimentazione
Angolo di scansione	Inclinazione 45 ° Elevazione 60 °
Dimensioni:	L165.42mm X W69.72mm X H89.67mm
Peso:	140g (senza supporto)
stare in piedi	Con
Colore:	Avorio e nero
Ambiente utente	
Temperatura di esercizio:	0 gradi C ~50 gradi C
Temperatura di conservazione:	-40 gradi C ~ 70 gradi C
Umidità:	5 ~ 95% di umidità relativa, senza condensa
Scarica elettrostatica:	CONFERMA a +/- scarico dell'aria 15KV e +/- 8KV di scarica a contatto
Goccia Specifiche:	Resiste a 1,5 m più cadute su cemento
Sicuro:	
EMI / RFI:	FCC Classe A e CE
Sicurezza laser:	Classe CDRH prodotto 2 laser



*Handheld Laser
Barcode Scanner*

OCBS-LA04



Product Picture





Features

Simple but not easy

Auto-Induction built in,
green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported



Durable construction combined with future-proofing



||| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	
Interface Supported:	RS2, RS232, USB

Interfaces supported:	RS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union

7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



