

Stampante termica Bluetooth Android pos 58 da 2 pollici con driver

(Modello: OCPP -586)

Specification:

| | |
|---------------------------------|---|
| Metodo di stampa | Termica diretta |
| Densità di stampa | 384 punti / linea (203 DPI) |
| Dimensione del personaggio | 384 punti / riga, carattere ANK, carattere: A: 12 * 24 punti, 1,5 (L) * 3,0 (A) mm Semplificato / tradizionale: 24 * 24 punti, 3.0 (W) * 3.0 (H) mm |
| Tipo di codice a barre | JAN13(EAN13)JAN8(EAN8)CODICE CODICE 39 (funzione opzionale) |
| Comando di stampa | Compatibile con EPSON ESC / POS |
| linguaggio | OEM437 / Katakana / OEM850 / OEM860 / OEM863 / OEM865 / Europa occidentale / Greco / Ebraico / Europa orientale / Iran / WPC1252 / OEM866 / OEM852 / OEM858 / IranII / Lettone / Arabo / PT151,1251 / OEM747 / WPC1257 / Vietnam / OEM864 / Hebrew / WPC1255 / Thai |
| Velocità di stampa | 90 millimetri / sec |
| Larghezza carta | 57,5 ± 0,5 millimetri |
| Spessore della carta | 0.06-0.08mm |
| MCBF (la vita) | 50 km |
| Dimensione | 190 * 132 * 119 millimetri |
| Peso lordo | 1.2KG |
| Taglierina automatica | taglierina manuale |
| Sensore | Sensore di fine carta, sensore di fine carta, sensore di apertura coperchio |
| Rotolo di carta | Φ75mm |
| Interfaccia | RS-232C, parallelo, USB, LAN |
| autista | Vinci 9 volte, Win 2000, Win 2003, Vinci XP, Vinci Vista, Win 7 Win8 Win10 compatibile con ESPON |
| Fornitura per stampante | DC12V / 3A |
| Controllo del cassetto contanti | DC12V / 1A |
| Temperatura di lavoro | 0-45°C, Umidità: 10-80% |
| Temperatura di risparmio | -10-60°C, Umidità: 10-90% |

Dettagli del prodotto:



**58mm Thermal
Receipt Printer**
OCPP-586



Product Picture





Features

Simple but not easy

Small size and elegant design





Can drive cash drawer



Compatible with ESPON



High printing speed



Printing head life: 50KM



All-round show





Application Area

Food delivery, restaurant, Traffic Citation,
Logistics, Transportation, Warehouse management,
Delivery, Illegal Parking Ticket, Drugstore,
Price Tag, Retail/Farm



Parameter

| | |
|------------------|---|
| Printing Method | Direct thermal |
| Print Density | 384dots/line (203DPI) |
| Character Size | 384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm |
| Barcode Type | JAN13 (EAN13) JAN8 (EAN8) CODE39 |
| Printing Command | Compatible with EPSON ESC/POS |
| Language | OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/ Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/OEM852/ OEM858/IranII/Latvian/ Arabic/PT151,1251/OEM747/ WPC1257/Vietnam/OEM864/Hebrew/WPC1255/Thai |
| Printing Speed | 90mm/sec |
| Paper Width | 57.5±0.5mm |
| Paper Thickness | 0.06-0.08mm |
| MCBF(life) | 50km |
| Dimension | 190*132*119mm |
| Gross Weight | 1.2KG |
| Auto Cutter | manual cutter |
| Sensor | Paper Near End Sensor, Paper End Sensor, Cover open sensor |
| Roll Paper | Φ75mm |
| Interface | RS-232C, Parallel, USB, LAN |

| | |
|---------------------|--|
| Driver | win 9X, win 2000, win 2003, win XP, win vista, win 7 compatible with ESPON |
| Printer Supply | DC12V/3A |
| Cash Drawer Control | DC12V/1A |
| Working Temperature | 0-45°C, Humidity: 10-80% |
| Saving Temperature | -10-60°C, Humidity: 10-90% |

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Connection



- a. Plug the DC cord connector into the printer's power connector..
- b. Plug the data cable connector into the printer's interface connector.
- c. Plug the drawer cable into the drawer kick-out connector on the back of the printer next to the interface connector.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on

3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.

