

**Lettores di codici a barre portatile ad alto livello con supporto  
(Modello: OCBS -LA09)**

**Specifica:**

Caratteristiche di performance	
Fonte di luce:	650nm visibile
Tasso di scansione:	200 scansioni al secondo
processore	32 bit
Distanza di lettura	2,5 ~ 600mm (100% UPC / EAN)
Larghezza della scansione	50mm @ 60mm, 220mm @ 200mm
Tipo di scanner:	Bidirezionale
Modalità di funzionamento	Senso automatico
Risoluzione:	Serie da 3mil ad alta risoluzione / 5mil long field field
Stampa contrasto minimo:	30%, differenza minima riflettente
Capacità di decodifica:	UPC / EAN, UPC / EAN con Supplementari, UCC / EAN 128, Codice 39, Codice 39 ASCII completo, Codice triplo 39, Codice 128, Codice 128 ASCII completo, Codabar, Interleaved 2 di 5, Discreto 2 di 5, Codice 93, MSI, codice 11, varianti RSS, cinese 2 di 5, MSI / Plessey, Regno Unito / Plessey, UCC / EAN 128, codice cinese, serie GS1 DataBar (RSS)
Angolo di scansione	± 65 ° (inclinazione); ± 60 ° (passo); ± 42 ° (imbardata)
Caratteristiche fisiche	
Interfacce supportate:	PS2, RS232, USB per opzione
voltaggio:	5 V CC ± 5%
Attuale:	85 mA (operativo); 100 (massimo)
Indicatore	Beeper, LED
Materiale	ABS + PC
stare in piedi	Con
Dimensioni:	156 * 68 * 83 mm (L * W * H)
Peso:	235g
Colore:	Grigio o nero
Ambiente utente	
Temperatura di esercizio:	0 °C ~ 45 °C
Temperatura di conservazione:	-40 °C ~ 60 °C
Umidità:	5% -90% (senza condensa)
Scarica elettrostatica:	Conforme a una scarica d'aria di +/- 15KV e +/- 8KV di scarico del contatto
Illuminazione ambientale	0 ~ 100.000 LUX
Drop specifiche:	Resiste a cadute multiple di 1,5 m sulla superficie del calcestruzzo
Classificazione laser	EN60825-1, Classe 1

**Dettagli del prodotto:**





## Features

**Simple but not easy**

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



## || All-round show





## Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
<b>Physical Characteristics</b>	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
<b>User Environment</b>	
Operating Temperature:	0℃~45℃
Storage Temperature:	-40℃~60℃
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.



**Documenti rilevanti:**

Vuoi sapere più prodotti informazione?per favore [Clicca qui.](#)

**specificazione**  
**Manuale utente**