

1. Good di OoOOSsiPUNzione del calore SisTeMa POS laVorar bene in un ambiente più duro
2. Super-Slim tocco SScreen display e design elegante migliora il tuo profilo più alto
3. More scientifico struttura separata per una facile manutenzione e smontaggio

Modello	- 1562-W	- 1562-A
Nome	15.6 pollice Tocco POS t Erminial	
Alloggio materiale	Allievo e base in lega di alluminio	
ScHermo principale	15.6 Monitor touch screen pollici , Pannello IPS	
Resolu zione	1920*1080	
Luminosità	220cd/m <sup>2</sup>	
Visualizzazione a ngle	Orizzonte: 90, Verticale: 60	
Touch s creen	Multi-punto Proiettato GG tocco capacitivo	
Sub- display	Display da 11,6 pollici W/ o w/ o toccare la funzione per l'opzione	
<b>Prestazione</b>		
Scheda madre	Intel Celeron J 6412, 2,0 GHz Intel core i3 CPU per l'opzione	Serie RockChip RK3 568 , Quad Core 2.0 G
Sistema m Emory	1*So-Dimm DDR 4 slot, Supporto 3200MHz, 4GB /8 GB /16G per opzione	A bordo di DDR4 4GB, 8G per l'opzione
Dispositivo di archiviazione	64 GB M.2 SSD o High ehm, fino a 512 GB	A bordo di 32 GB EMMC 64 GB per l'opzione
Lan /Wlan	10/100 /1000 MBS, Realtek RTL8111F LAN CHIP Incorporato in mini slot PCI-E, supporto WiFi incorporato supporto	10/100 /1000 MBS, Realtek RTL8111F LAN CHIP Supporto Wi-Fi 802.11 UN/ b/g/n , BT3.0/BT4.0
Operativo s ystem	Finestre 10/11	Android 11
<b>Connettività</b>		
Esterno I/O port J 6412	Power pulsante*1	
	12V DC in Jack*1	
	LAN: RJ-45*1 , USB*6, com*2, mini hdmi*1	
	Allinea e microfono in 2in1 jack *1	
Esterno Porta I/O RK3568	Power pulsante*1	
	12V DC in jack*1	
	LAN: RJ-45*1 , USB*6, com*1	
	Allineate*1	
<b>Ambiente</b>		
Temperatura operativa	0 a 50 gradi centigradi	
Temperatura di conservazione	-20 a 60 gradi centigradi	
Umidità funzionante	10%~90% Nessuna condensa	
Umidità di conservazione	10%~90% Nessuna condensa	
<b>Pacchetto</b>		
Peso	Net Peso 3.6K g , g Ross peso 4.9k g	
Pacchetto con schiuma all'interno	430*240 * 370 mm per uno schermo singolo	
<b>Accessori</b>		

Adattatore di potenza	110-240 V/50-60Hz AC Potenza i nput , DC12 V /5a adattatore di output
Cavo di alimentazione	Perca del cavo di alimentazione compatibile con USA / UE / UK ecc.



## Super Slim Die-cast Aluminum Touch POS Terminal

Model: POS-1562



Super Slim



Die-cast Aluminum



Waterproof



Windows/Android



### 10mm Ultra-thin Body

High-end titanium gray color.  
Modern stylish, industry new innovation.




### Full Die-cast Aluminum Body

Uniform and delicate oxidized color,  
more advanced than the painting process.



### Full Lamination Advantage

Improved light transmittance ensure  
high-definition display and higher  
brightness to compatible with outdoor use.  
Dust-free makes the screen cleaner.



### Waterproof

Improved waterproof performance of the  
surface, to avoid accidental water ingress.



### High-Efficiency

Configurated DDR4 3200MHz RAM and NVME  
protocol M.2 SSD, faster response when operate.



### Scientific Structural Design

Mainboard is sticked behind of lcd screen  
ensuring maintenance convenient and  
well-done cables management.



## Specifications



**OS**  
Windows 10/11  
Android 11



**Processor**  
Intel Celeron J6412  
Rockchip RK3568



**Memory**  
DDR4 4GB/8GB/16GB



**Storage device**  
128G/256G/512G SSD  
32G/64G/128G eMMC



**Main screen**  
15.6" LCD (1920\*1080)  
16:9, Multi-point projected G+G capacitive touch



**Sub-display**  
11.6"  
Touch function for option



**Interface**  
USB2.0\*4, USB3.2\*2, RJ48(Serial)\*2,  
1000Mbps LAN\*1, Mini HDMI\*1,  
12V 5A DC input\*1, Audio\*1



**Housing material**  
Aluminium alloy  
Titanium grey



**Options**  
3W Speaker  
Wifi&Bluetooth  
4G LTE



**Environment**  
Operating temperature: 0°C - 50°C  
Storage temperature: -20°C - 60°C



**Size (W\*H\*D)**  
Product size: 370\*180\*296(mm)  
Packaging size: 430\*240\*390(mm)



**Weight**  
Net: 3.55kg  
Gross: 4.9kg

Notice: Product specifications subject to change without prior notice. Product pictures are taken with engineering sample. OCOM reserves the right to change the product information without prior notice.

Website: [www.ocominc.com](http://www.ocominc.com)









