

## POS LED clienti Pole display (Modello: LED8A)

### Specifiche tecniche:

Comunicazione	
Interfaccia:	RS232 comunicazione, alimentatore USB (DC opzionale)
Baud rate:	2400/9600BPS
Luminosità:	1500cd
Stretta di mano segnale	No
Elettrico	DC5V (Dall'interfaccia USB del computer host)
Display:	LED Giallo-verde brillante display digitale
Visualizza caratteri:	8 numeri (0 ~ 9)
Area di visualizzazione:	160 millimetri 30,8 millimetri x
Dimensione dei caratteri:	13MM * 7.6mm
MTBF:	25.000 orario
Fisico	
Pannello Dimensioni:	224 (L) X88 (W) mm
Supporto Dimensioni:	Altezza: 400 --- 442 millimetri Base: 185 (L) x95 (w) x25 (H) mm
Pitching mosca Angolo:	8 ° ~ 120 °
Colore	Bianco o Nero
Peso:	520g (senza base), 850g (con la base); 1100g (compreso l'imballaggio)
Formato dell'imballaggio	255 (L) x 210 (W) x 96 (H) mm
Ambiente	
Operativo Temp:	-40 °C - 50 °C
Conservazione Temp;	-60 °C - 80 °C
Umidità:	30% - 85%

### Dettagli di prodotto:



LED Customer Display  
LED8A



Product Picture





## Features

### *Simple but not easy*

8 characters LED display;





Pole height is adjustable;  
360 degree rotation angel;



Compatible with "ESC / POS"  
standard common instruction set,  
no need driver, plug and use;



## All-round show





## Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop  
Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop  
Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket



Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf



## Parameter

Communication	
Interface:	RS232 communication, USB power supply (DC optional)
Baud rate:	2400/9600BPS
Brightness:	1500cd
Handshake signal	No
Electrical	DC5V (from host computer USB interface)
Display:	LED Bright yellow-green digital display
Display characters:	8 Numbers (0~9)
Display area:	160mm ×30.8mm
Font size:	13MM*7.6MM
MTBF:	25,000 hours
Physical	
Panel dimensions:	224(L)X88(W)mm
Support dimensions:	Height: 400—442mm Base: 185(L) x95(w) x25(H) mm
Pitching move angle:	8°~120°
Color	White or Black
Weight:	520g (without base); 850g (with base); 1100g (including packing)
Packing Size	255(L) x 210(W) x 96(H) mm
Environment	

Operating Temp:	-40°C--50°C
Storage Temp:	-60°C--80°C
Humidity:	30%--85%

## Production Line



## Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

## Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6



✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Certifications



## Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protective film



CHINA POST

## Payment



## Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





## Why you choose us?



This Assessed Supplier Has Been  
Independently Verified

Build Your Growth On Trust



**TÜVRheinland®**  
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of the leading suppliers of POS and Auto-ID related products from China.

OCOM's product portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and are hot selling in Europe, Australia, Asia, and other areas.

OCOM has a professional team including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales have more than 5 years' experience, which helps us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like to establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

**Sales Center:**

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,  
Shenzhen 518054, China;

Websites: <http://www.possolution.com.cn> ; <http://www.ocominc.com> ;

E-mail: [ocom@ocominc.com](mailto:ocom@ocominc.com) , [ocomtech@gmail.com](mailto:ocomtech@gmail.com) ;

Skype: ocominc2000, ocominc;

MSN: [ocomtech@hotmail.com](mailto:ocomtech@hotmail.com), [ocominc@hotmail.com](mailto:ocominc@hotmail.com);

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



## **I documenti rilevanti:**

**Vuoi saperne di più inf prodottoormazione?Per favore Clicca qui.**

[Specificazione](#)

[Manuale d'uso](#)

[Autista](#)