

Mini usb del codice a barre del laser scanner

(OCB-LA11)

Caratteristica:

☒ Codice a barre laser 1. Handheld scanner con funzione di rilevamento automatico;

Operazione 2. Flexible con 360 gradi supporto in metallo rotazione;

Velocità di scansione 3. high (100 scansioni / sec) elunga distanza di lettura;

Capacità di decodificare 4. Excellent;

5. KBW, RS232 e USB supportati;

6. Grey e colore nero disponibile

Specifica:

Prestazione Caratteristiche	
Leggero Fonte:	Visibile laser (650-670nm)
Scansione Voto:	100 scansioni al secondo
Lettura Distanza	2.5 ~ 600 millimetri (100% UPC / EAN)
Tipo di scanner:	Bidirezionale
Risoluzione:	0,10 millimetri (4mil) a PCS 0.9
Contrasto di stampa minimo:	30%, riflettente minima Differenza (@ 650nm)
Error Rate:	1/3000000
Capacità di decodifica:	UPC / EAN, UPC / EAN con Supplementals, UCC / EAN128, il codice 39, codice 39 ASCII completa, codice 39 Trioptic, codice 128, codice 128 ASCII completa, Codabar, Interleaved 2 of 5, discreto 2 su 5, codice 93, MSI, codice 11, ATA, varianti RSS, cinese 2 di 5 ...
Fisico Caratteristiche	
Interfacce supportate:	PS2, RS232, USB
voltaggio:	DC + 5V +/- 5%
Corrente:	100 mA
Idle corrente:	& lt; 40 mA
Fonte di potere:	Host potere o esterna (RS232) Alimentazione
Angolo di scansione	Inclinazione 45 ° Elevazione 60 °
Dimensioni:	L165mm X W63mm X H87mm
Il peso:	129g (senza supporto)
Stare in piedi	Opzionale
Colore:	Grigio e nero
Utilizzatore Ambiente	
Operativo Temperatura:	0 °C ~ 40 °C
Conservazione Temperatura:	-40 °C ~ 60 °C
Umidità:	5 ~ 95% di umidità relativa, senza condensa
Elettrostatica Scarico:	Conferma per +/- Scarico dell'aria 15KV e +/- 8KV di scarica a contatto
Goccia Specifiche tecniche:	Resiste 1.5m più cadute su cemento
Al sicuro:	

EMI / RFI:	FCC Classe A e CE
Laser di sicurezza:	CDRH Class 2 prodotto laser



Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.

