Stampante diretta per etichette termiche

(M / n: OCBP -010.)

Caratteristiche:

Supporta il comando TSPL per la stampa di etichette

Supporta il comando ESC / POS per la stampa della ricevuta

Velocità di stampa alta 160mm / s

Fornire il software di realizzazione dell'etichetta gratuita

Porta carta esterna per facoltativo

Specifiche	
Interfacce	USB (standard), USB + LAN, USB + BT, USB + LAN (opzionale)
Stampa COMAND.	TSPL / ESC / POS
Metodo di stampa	Stampa termica
PIRNT VELOCE.	160 mm / sec.
Risoluzione	203 DPI.
Taglierina di carta automatica	NO
Stampa Larghezza	104mm (max)
Sistema operativo compatibile	Win9X / Win2000 // Win2003 / Win Vista / Win 7 / Window XP / Win 8 / Win8.1 / Win 10 / IOS / Android
Carta	
Tipo	Rotolo di carta
Larghezza	110 ± 0,5mm.
Spessore della carta	0,06-0.3mm.
Elettrico	
Potenza	DC 24V / 2.5A
Stampa Affidabilità	100 km
Ambientale	
Temperatura	Lavorare: da 0 a 50 gradi
Umidità	Lavoro: 20% -85%
Altre caratteristiche	Stampa audace / Carattere Regolazione / Linea Spacing Setting supportata / 1D e QR Stampa a barre e PDF417

Aocom®
At your side

OCBP-010

ISO FC CE RoHS

Aocom®
At your side

OCBP-010

ISO FC CE RoHS

Aocom®
At your side

OCBP-010

ISO FC CE RoHS

Aocom®
At your side

OCBP-010

Aocom®
At your side

OCBP-010

Aocom®
At your side

OCBP-010

ISO FC CE RoHS

Aocom®
At your side

OCBP-010

Aocom®
At your side
OCBP-010
LABEL PRINTER
Instruction Manual
ISO
FC
CE
RoHS

Aocom®
At your side

OCBP-010

ISO FC CE RoHS