

Mini lettore di codici a barre portatile Auto Sense con supporto (Modello: OCBS -LA11)

Caratteristica principale:

Scanner di codici a barre laser palmare 1D con funzione di rilevamento automatico;
Funzionamento flessibile con supporto metallico a rotazione a 360 gradi;
Alta velocità di scansione (100 scansioni / sec) e lunga distanza di lettura;
Eccellente capacità di decodifica;
KBW, RS232 e USB supportati;
Colore grigio e nero disponibili;

SPECIFICHE TECNICHE:

| | |
|--------------------------------|--|
| Caratteristiche di performance | |
| Fonte di luce: | Laser visibile (650-670 nm) |
| Tasso di scansione: | 100 scansioni al secondo |
| Distanza di lettura | 2,5 ~ 600mm (100% UPC / EAN) |
| Tipo di scanner: | Bidirezionale |
| Risoluzione: | 0.10mm (4mil) a PCS 0.9 |
| Stampa contrasto minimo: | 30%, differenza minima riflettente (@ 650nm) |
| Tasso di errore: | 1/3000000 |
| Capacità di decodifica: | UPC / EAN, UPC / EAN con integratori, UCC / EAN128, codice 39, codice 39 ASCII completo, codice 39 trioptic, codice 128, codice 128 ASCII completo, codabar, interleaved 2 su 5, discreto 2 su 5, codice 93, MSI , codice 11, ATA, varianti RSS, cinese 2 di 5 ... |
| Caratteristiche fisiche | |
| Interfacce supportate: | PS2, RS232, USB |
| voltaggio: | CC + 5V +/- 5% |
| Attuale: | 100 mA |
| Corrente inattiva: | < 40 mA |
| Fonte di potere: | Alimentazione host o alimentazione esterna (RS232) |
| Angolo di scansione | Inclinazione 45 ° Altezza 60 ° |
| Dimensioni: | L165mm X L63mm X H87mm |
| Peso: | 129g (senza supporto) |
| stare in piedi | Opzionale |
| Colore: | Grigio e nero |
| Ambiente utente | |
| Temperatura di esercizio: | 0 °C ~ 40 °C |
| Temperatura di conservazione: | -40 °C ~ 60 °C |
| Umidità: | 5 ~ 95% di umidità relativa, senza condensa |
| Scarica elettrostatica: | Confermare a +/- 15KV di mandata dell'aria e +/- 8KV di scarico del contatto |
| Drop specifiche: | Resiste a cadute multiple di 1,5 m sul cemento |
| Sicuro: | |
| EMI / RFI: | FCC Classe A e CE |
| Sicurezza laser: | Prodotto laser CDRH classe 2 |

Dettagli del prodotto:



ocom
All your side

*Handheld Laser
Barcode Scanner*

OCBS-LA11

Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



||| All-round show





Parameter

| Performance Characteristics | |
|-----------------------------|--|
| Light Source: | Visible laser (650-670nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance: | 2.5 ~600mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) at PCS 0.9 |
| Print Contrast Minimum: | 30%, minimum reflective difference (@650nm) |
| Error Rate: | 1/3000000 |
| Decode Capability: | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |

| Physical Characteristics | |
|---------------------------------|--|
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | DC+5V+/-5% |
| Current: | 100 mA |
| Idle Current: | <40 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L165mm X W63mm X H87mm |
| Weight: | 129g (without stand) |
| Stand | Optional |
| Color: | Grey and black |
| User Environment | |
| Operating Temperature: | 0°C~40°C |
| Storage Temperature: | -40°C~ 60°C |
| Humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| Safe: | |
| EMI/RFI: | FCC Class A and CE |
| Laser Safety: | CDRH class 2 laser product |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.





Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: ocomsales01; **MSN:** ocomsales01@hotmail.com

Ali TM: cn1001868228; **QQ:** 1483705401

Mobile/Wechat/Whatsapp: 0086.18948713992



Reliable One-Stop Supplier for POS and Auto-ID Related Products