

Ultimo lettore di codici a barre con immagine 2D senza mani

Può leggere l'acquisizione e la decodifica dell'immagine

Scansione omnidirezionale, facile da scansionare

Flatbed desktop & Design conciso

Con stand & costante modulo scanner affidabile

Acquisizione e decodifica di immagini ad alta velocità

Parametri di prestazione	
Fonte di luce	LED bianco
Cicalino	Sette toni o silenziosi
Lampada	bianca
Interfaccia di sistema	KBW, RS232, USB
Parametri fisici	
Volume (Lx W x H)	Dimensioni del prodotto 78 mm x 75 mm x 141 mm (3,2? X 3,3? X 5,9?),
Peso	Formato del prodotto 180 g (12 once)
Parametri elettrici	
Tensione di ingresso	5,5 VCC \pm 0,25 V
Potenza di lavoro	2,0 W (430 mA a 5 V)
Potenza in standby	0,5 W (100 mA a 5 V)
Parametro ambientale	
Temperatura di esercizio	0 ° C - 40 ° C
Temperatura di conservazione	-40 ° C -60 ° C
Umidità	Umidità relativa da 0% a 95% (senza condensa)
Caratteristica antiknock	Resiste a un'altezza di 1,5 metri dal pavimento in cemento.
A prova di polvere	Sigillare per prevenire l'erosione delle particelle di polvere d'aria.
Parametri di scansione	
Modalità di scansione	Omni direzionale (640X480)
Massima riflettività	È possibile leggere una riflettività massima del 20%
Angolo di scansione	70 °, 75 °



Hand free Imaging Scanner for 2D Barcode

OCBS-T201



Product Picture



Features:

Reliable with good price

High speed image acquisition and decoding



Can read the barcode on the screen



Omni-directional scanning, easy to scan





▼ **With steady stand & reliable scanner module**

▼ **Desktop flatbed & Concise design**



Application place



Bookstore



Supermakte



Pharmacy



Warehouse



Clothing store



Restaurant

Parameter

Performance parameters	
Light source	white LED
Buzzer	Seven tones or silent
Lamp	White
System interface	KBW, RS232,USB
Physical parameters	
Volume(Lx W x H)	Product size 78 mm x 75 mm x 141mm (3.2" x 3.3" x 5.9"),
Weight	Product size180 g (12 oz)
Electrical parameters	
Input voltage	5.5 VDC ± 0.25 V
Work power	2.0 W (430 mA @ 5 V)
Standby power	0.5 W (100 mA @ 5 V)
Environmental parameter	
Operating temperature	0° C - 40° C
Storage Temperature	-40°C -60°C
Humidity	0% to 95% relative humidity (no condensation)
Antiknock characteristic	Withstand 1.5 meters high drop from concrete floor.
Dust-proof	Seal to prevent air dust particle erosion.
Scanning parameters	
Scanning mode	Omni directional (640X480)
Highest Reflectivity	Max 20% reflectivity can be read
Scanning Angle	70°, 75°

Quality Assurance:



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services.

OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:




Warranty and After Sales:



- ▶ All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- ▶ Spare parts will be provided for mass orders for customers' local maintenance.
- ▶ Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- ▶ Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- ▶ Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- ▶ Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- ▶ 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:



Payment:



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Company Profile

TRADE ASSURANCE

- 100% money refund for Late shipment & Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Documenti rilevanti:

[manuale utente](#)