

## Mini portatile scanner di codici a barre 1D Bluetooth (Modello: OCB-W106)

### Specifica:

Hardware		
2D CMOS		
Sensor	CMOS 640x 480	
Simbologie	La maggior parte dei 1Ds e PDF 417, QR Code, dati Matrix, codice Maxi, Aztec, etc.	
Distanza di lettura	UPC / EAN / 13 mil	30-205 mm
	Codice 39/20 mil	30 305 mm
	PDF 417/10 mil	50-155 mm
	Data Matrix / 15 mil	52-155 mm
1D LASER		
Fonte Di Luce	Diodo laser visibile, lunghezza d'onda di 650nm	
Scanner Tasso	200 scansioni al secondo (SPS)	
Risoluzione	0,1 millimetri (4mil) a PCS 0.9	
Lettura Distanza	1 a 80cm (risoluzione dipendente)	
Angolo di inclinazione	45 gradi	
Angolo Skew	65 Degree	
PCS	0.3	
Potere		
Voltaggio Requisito	DC + 5V 5%	
Picco Corrente	98mA	
Corrente Idle	63mA	
Ambiente		
Temperatura	Funzionamento: -10 gradi C -50 gradi C Conservazione: -20 gradi C-60 gradi C	
Umidità	Funzionamento: 5% -95% (senza condensa) Stoccaggio: 5% -95% ( senza condensa)	
Shock	2.5m goccia sulla superficie di calcestruzzo	
EMI Generation	FCC	
Sicurezza	Classe CDRH Prodotto 1 laser	
Luce Ambientale	Max.10, 000 Lux (FL)	
Fisico		
Taglia	123mmx54mmx29mm	
Peso	216g (con cavo)	
Lunghezza del cavo	1.8m	
Bluetooth		
Comm Dist	10m / 100m	
Comunicazione	Built-in SPP e HID	
Modo	Master o Schiavo	
Corrente Consumo	1 88mA	
Inattivo Corrente	93mA	
Batteria	Li-ion 950mAH	
Lavoro Orario	& Gt; 10 ore	
Memoria	Memoria 4M	
Informazioni Sull'ordine		
OCB-W106	Mini Portable Scanner Bluetooth 1D codici a barre	
OCB-W206	Mini Portable Scanner Bluetooth 2D Barcode	

### Scheda Prodotto:



***Mini Bluetooth  
1D/2D Barcode Scanner  
OCBS-W106/W206***




**Product Picture**



## Features

### Simple but not easy

1D - Laser 650nm,  
2D - CMOS 300K million pixels;



Mini size, as small as 123\*54mm, 110 grams without cable;  
Durable Construction: 2.5m Shock resistant;  
Bluetooth Communication: Class I/II (10m/100m);



Impressive Scan Rate:  
1D - about 200SPS,  
2D - 600MHz Processor;




Built-in SPP and HID;  
512MB memory;  
Master/Slave Switchable;  
900mAH Li-ion Battery;

Recharged by USB cable  
or cradle (optional);



## ||| All-round show





## Parameter

Hardware		
<b>2D CMOS</b>		
Sensor	CMOS 640x 480	
Symbologies	Most 1Ds and PDF 417, QR Code, Data Matrix, Maxi code, Aztec, etc.	
Reading Distance	UPC/ EAN /13 mils	30 to 205 mm
	Code 39/ 20 mils	30 to 305 mm
	PDF 417 /10 mils	50 to 155 mm
	Data matrix /15 mils	52 to 155 mm
<b>1D LASER</b>		
Light Source	Visible laser diode, wavelength 650nm	
Scanner Rate	200 scans per seconds(SPS)	
Resolution	0.1mm(4mil) at PCS 0.9	
Reading Distance	1 to 80cm(resolution dependent)	
Tilt Angle	45 Degree	
Skew Angle	65 Degree	
PCS	0.3	
Power		
Voltage Requirement	DC+5V 5%	

<b>Peak Current</b>	98mA
<b>Idle Current</b>	63mA
<b>Environment</b>	
<b>Temperature</b>	Operation:-10 Degree C -50 Degree C Storage:-20 Degree C-60 Degree C
<b>Humidity</b>	Operation:5%-95%( non-condensing) Storage:5%-95%( non-condensing)
<b>Shock</b>	2.5m drop on concrete surface
<b>EMI Generation</b>	FCC
<b>Safety</b>	CDRH class 1 laser product
<b>Ambient Light</b>	Max.10 ,000 Lux(FL)
<b>Physical</b>	
<b>Size</b>	123mmx54mmx29mm
<b>Weight</b>	216g(with cable)
<b>Cable Length</b>	1.8m
<b>Bluetooth</b>	
<b>Comm Dist</b>	10m/100m
<b>Communication</b>	Built-in SPP and HID
<b>Mode</b>	Master or Slave
<b>Current Consumption</b>	1 88mA
<b>Idle Current</b>	93mA
<b>Battery</b>	Li-ion 950mAH
<b>Working Hours</b>	>10 hrs
<b>Memory</b>	4M memory
<b>Ordering Information</b>	
OCBS-W106	Mini Portable Bluetooth 1D Barcode Scanner
OCBS-W206	Mini Portable Bluetooth 2D Barcode Scanner

### Related Parts:

1D Engine



2D Engine



Dimensions	42x45x17mm
Working Current	42mA @ 5V
Infrared Sensor	Auto trigger
Output Signal	TTL

Dimensions	28x14x8mm
Power consumption	42mA @ 3.3V
Output Signal	TTL

## Production Line



## Capacity

Model

Product Name

Production Line Capacity

Actual Units Produced/Orders Month

Capacity

verified	Product Name	Production Line Capacity	Actual Units Produced (Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

## Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6


✓	Withstand voltage tester	UC29/UA	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No information	13

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Certifications



## Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protective film



## Payment



## Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





## Why you choose us?



## Company Profile

This Assessed Supplier Has Been  
**Independently Verified**

Build Your Growth On Trust



**TÜVRheinland®**  
Precisely Right.



OCOM Technologies Limited, founded in 2007, is one of the leading suppliers of POS and Auto-ID related products from China.

OCOM's product portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and are hot-selling in Europe, Australia, Asia, and other areas.

OCOM has a professional team including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years. All of the sales staff have more than 5 years of experience, which helps us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like to establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

**Sales Center:**

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,  
Shenzhen 518054, China;

Websites: <http://www.thermalprinter.com.cn> ; <http://www.ocominc.com> ;

E-mail: [ocom@ocominc.com](mailto:ocom@ocominc.com) , [ocomtech@gmail.com](mailto:ocomtech@gmail.com) ;

Skype: ocominc2000, ocominc;

MSN: [ocomtech@hotmail.com](mailto:ocomtech@hotmail.com), [ocominc@hotmail.com](mailto:ocominc@hotmail.com);

Trademanager: [szocominc, cn1500439666](https://www.alibaba.com/trade-manager?spm=2111.1.0.0.0);

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



## I documenti rilevanti:

Vuoi saperne di più inf prodottoormazione?Per Favore Clicca qui.

[Specificazione](#)