Bluetooth o Wireless 433MHZ 2D Barcode Scanner (OCB-W230 / OCB-W230B)

Parametri:

| Mirare | 617 LED nm |
|------------|--|
| Fonte Di | |
| Luce | |
| Illuminazi | 625 LED nm |
| one Fonte | |
| Di Luce | |
| Lettura | 39 ° (H) x 25 ° (V) |
| Angolo | |
| Rotazione | 0 - 360 ° |
| Angolo | |
| Elevazion | ± 65 ° |
| e Angolo | |
| Inclinazio | ± 60 ° |
| ne Angolo | |
| Stampa | Superiore al 25% |
| Contrasto | |
| 1D | UPC / EAN, UPC / EAN con Supplementals, BooklandEAN, ISSN, UCC Coupon estesa |
| | Codice, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, |
| | Codice 32, Codice 93, Code11, Matrix 2 di 5, Interleaved 2 of 5, Discrete 2di 5, |
| | Codabar, MSI, cinese 2 di 5, GS1 Dati Barvariants, coreano 3 su 5, ISBT Concat |
| 2D | PDF417, MicroPDF417, codici compositi, TLC-39, i dati Matrix, Maxicode, QR Code, |
| | MicroQR, Aztec |
| Interfacci | USB |
| a | |
| 1 | Interno: 100m; Esterno: 300m (max) |
| zione | |
| distanza | |
| Operativo | -10 ° C - 45 ° C |
| Temperat | |
| ura | |
| Immagazz | -20 ° C - 65 ° C |
| inamento | |
| Temperat | |
| ura | |
| Operativo | 2% -82% |
| Umidità | E0/ 0E0/ |
| Immagazz | 370 - 93% |
| inamento | |
| Umidità | Desiste 1 9m niù cadute su comente |
| | Resiste 1.8m più cadute su cemento |
| Za | DC 5V 250mA |
| 5 | DC 5V, 350mA |
| Potere | Internal 2 000 LUV may, Luca calara Estarra: 00000 LUV |
| | Interno: 3.000 LUX max; Luce solare Esterno: 86000LUX max |
| n | |

| EMC EN50081, norma | par1 | | | |
|-----------------------------|-----------------------------------|------------------------|----------------|--|
| FCC EN50082, norma | CC EN50082, norma par1 | | | |
| IP Grado IP42 | | | | |
| DECODE CAMPI | | | | |
| Prestazioni tipiche * | | Campi di lavoro tipici | | |
| riestazioni tipicne | | HD Gamma del fuoco | | |
| Bar Codice Tipo | Simbolo Densità | Vicino | Lontano | |
| Codice 39 | 5,0 mil | 5 millimetri | 90 millimetri | |
| 100% UPCA | 13,0 mil | 8 millimetri | 200 millimetri | |
| Codice 39 | 20,0 mil | 8 millimetri | 250 millimetri | |
| PDF 417 | 6.8 mil | 5 millimetri | 95 millimetri | |
| Dati Matrice | 10,0 mil | 5 millimetri | 110 millimetri | |
| QR Codice | 20,0 mil | 10 millimetri | 150 millimetri | |
| Risoluzione 1D Codice 39 | 2.8 mil (0,071 millimetri) | | | |
| Risoluzione 2D Data Matrix | latrix 4.8 mil (0,122 millimetri) | | | |
| Materiale | ABS + PC | | | |
| Dimensione | 95x65x155mm | | | |
| Rete Peso | 160g | | | |
| Interno Dimensione scatola: | 18.2X11.7X11.2cm | | | |
| nterno Peso scatola: 374g | | | | |





Bookstore



Supermaket




Pharmacy





Warehouse





Restaurant

| Parame | eter | | |
|--------------------------|-------------|--|--|
| Physical Characteristics | | | |
| Dimension | 95x65x155mm | | |
| Material | ABS+PC | | |
| Net Weight | 160g | | |

| At | C17 | Optical Performance | - Com | | |
|--------------------------|----------------------------|---|--|-------------------------|--|
| Aiming Light Source | 617 nı | | 11 | | |
| Lighting Light Source | | 625 nm LED | | | |
| Scanning Angle | |) x 25° (V) | | N. U. | |
| Rotation Angle | 0 - 360 |), | | 100 | |
| Elevation Angle | ± 65° | - N | (A) | -1 | |
| Tilt Angle | ± 60° | #1W2##00000####99990 | | | |
| Print Contrast | | Higher than 25% | | | |
| 1D | Coupo FullAS Interle | on Extended Code, Code128, CII, Trioptic Code 39, Code | ementals, BooklandEAN, IS GS1-128, ISBT 128, Code 39 32, Code 93, Code11, Matr 5, Codabar, MSI, Chinese 2 T Concat | , Code 39 ix 2 of 5, | |
| 2D | TATE OF STREET | 7, MicroPDF417, Composite de, MicroQR, Aztec | Codes, TLC-39,Data Matrix, N | Maxicode, | |
| Interface | USB | 2004. vol 1 0014041404.00000000000000000000000000 | | | |
| Communication distance | Inside | : 100m; Outside: 300m (Ma | ax) | | |
| Operating Temperature | -10°0 | C -45℃ | Mc.co | | |
| Storage Temperature | -20°C | C -65°C | | 00 | |
| Operating Humidity | 5%-85% | | | | |
| Storage Humidity | 5%-95 | % | la. | N. | |
| Durability | Withs | tands multiple 1.8m drops to | concrete | | |
| Input Power | DC 5V, 350mA | | | | |
| Lumination | Inside | : 3.000 LUX max; Outside | sunlight: 86000LUX max | | |
| EMC | EN500 | 81, par1 standard | | | |
| FCC | EN500 | 82, par1 standard | | | |
| IP Grade | IP42 | | | | |
| | | DECODE RANGES | | 674 | |
| Typical Performance* | | | Typical Working Ranges | | |
| | | | HD Focus Range | | |
| Bar Code Type | | Symbol Density | Near | Far | |
| Code 39 | | 5.0 mil | 5mm | 90mm | |
| 100% UPCA | VOII. | 13.0 mil | 8mm | 200mm | |
| Code 39 | | 20.0 mil | 8mm | 250mm | |
| PDF 417 | | 6.8 mil | 5mm | 95mm | |
| Data Matrix | | 10.0 mil | 5mm | 110mm | |
| QR Code | | 20.0 mil | 10mm | 150mm | |
| Resolution 1D Code 39 | | -AV | 2.8 mil (0.071mm) | N II | |
| Resolution 1D Code 3 | 9 | | 2.0 11111 (0.07 1111111) | 1111 | |



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers'satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist.

Test Equipment and Facilities

| Verified | Machine Name | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| 1 | Ageing Tester | No Information | 6 |
| 1 | Withstand Voltage Tester | CC2670A | 1 |
| 1 | Oscilloscope | TBS1102 | 1 |
| 1 | DC Power Supply | PS-305DM | 6 |
| 1 | Digital Torque Meter | HP100 | 1 |
| 1 | Calliper | GUANGLU | 2 |
| 1 | Multi-meter | VC890D | 7 |
| 1 | Test Computer | No Information | 13 |

Verified by TUV on 2013.7.15

Certification:









Warranty and After Sales:

- All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.































secure payment







Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.





Company Profile



TRADE ASSURANCE

- 0100% money refund for Late shipment&Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba
- in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers, Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs. OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.















Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn; E-mail: ocom@ocominc.com, info@possolution.com.cn;

Tel: +86.755.86053207 ext 800; Fax: +86.755.86053207 ext 868; QQ: 2485890637, 190852203; Wechat: szocominc, hj34924238; Whatsapp: 008613352932860;



I documenti rilevanti:

- *Specificazione
- * Manuale Utente