

Di alta qualità 433 MHz o Bluetooth wireless QR code scanner a barre 2D con supporto

Modello: OCBS-W231-4/b

Caratteristiche:

- 1, 433 MHz distanza di comunicazione wireless 300 m Outdoor, interno 100 m; La distanza dal wireless Bluetooth Outdoor 20 m e 10 m indoor;
- 2, dotato della carica e della comunicazione
- 3, una copertura di plastica morbida per proteggere la lente e un contorno migliora significativamente le prestazioni di Anti-Drop;
- 4, codici a barre sullo schermo di computer e telefoni cellulari possono essere scansionati;
- 5, non hai bisogno di driver, plug & Play;
- 6, può immagazzinare più di 10 000 parti dei dati;
- 7, è possibile collegare più scanner a un solo ricevitore (433 MHz).

Parametri:

Avere una sorgente luminosa	617 nm LED
Illuminazione sorgente luminosa	625 Nm LED
Angolo di scansione	39 ° (h) 25 ° (v)
L'angolo di rotazione	0-360 °
Angolo di elevazione	65 °
Angolo di inclinazione	60 °
Contrasto di stampa	Superiore al 25%
1 d	UPC/EAN, UPC/EAN con supplementi, BooklandEAN, ISSN, coupon UCC Extended Free Code128, GS1-128, ISBT 128, codice 39, codice 39 Full ASCII, codice 39 Trioptic, codice 93, codice 32, Code11, Matrix 2 5, Interleaved 2 di 5, discreto 2of 5, Codabar, MSI, 2,5, Barvariants data, GS1, coreano 3 5, ISBT Concat
2D	Tipo di PDF417, MicroPDF417, codici complessi, TLC-39, Datamatrix, MaxiCode, QR code, Aztec, MicroQR
Interfaccia	USB (ricevitore wireless via cavo)
Gamma di comunicazione	433 MHz: interno: 100 m; Fuori: 300 m. (max.) Bluetooth: interno: 10 m; Esterno: 20 m (max.)
Temperatura di funzionamento	-10 gradi c-45 gradi c
Temperatura di stoccaggio	-20 ° c-65 ° c
Umidità di funzionamento	5-85%
Contenuto di umidità durante la conservazione	5%-95%
La durata del	Può sopportare una varietà di 1,5 m a calcestruzzo
Ingresso alimentazione	5 v CC, 280mA
Tempo di ricarica	6 h
Batteria	1500mAh

Luminanza	Interno: 3.000 lux max; Luce solare: max 86000 Lux		
Grado IP	IP42		
Intervalli di decodifica			
Una performance tipica *	Gamme operative tipiche		
	Focus range HD		
Tipo di codice a barre	La densità dei simboli	Vicino	Molto
Il codice 39	5,0 km	5 mm	90 mm
100% dei codici a barre UPCA	13,0 km	8 mm	200 mm
Il codice 39	20,0 km	8 mm	250 mm
PDF 417	6,8 km	5 mm	95 mm
La matrice di dati	10,0 km	5 mm	110 mm
Codice QR per	20,0 km	10 mm	150 mm
Risoluzione 1 codice d 39	4 mil		
La risoluzione della matrice di dati 2D	10 mil		
Materiale	ABS + PC		
Una dimensione	Base scanner (70 * 95 * 168 mm) (145 * 112 * 74 mm)		
Peso netto	Scanner 185 g base 186 g		
Informazioni sull'ordinazione:	OCBS-W231-4: scanner di codici a barre 2D wireless 433 MHz dalla culla		
	OCBS-W231-b: scanner 2D con Barocde Bluetooth Cradle		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT
INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

ocominc.com

ocominc