

Stampante termica della ricevuta di posizione di 80mm-URL di OCPP-80E con la taglierina automatica per il ristorante (Modello n .: OCPP-80E-URL)

A.Features:

- 1.Desktop o tipo a parete per opzione.
2. Supporta multi codici a barre 1D e stampa di codici 2D.
- Porta Ethernet da 3.100M, trasmissione dati ad altissima velocità.
- 4.Supporta memoria Logo NV da 256KB e memoria buffer grande da 2M.
- 5.Supporta la funzione di promemoria degli ordini, compatibile con il driver OPOS.e rilevamento del segno nero(Opzionale)
6. Supporta il monitoraggio dello stato di stampa e la funzione di ordine anti-perdita.

B. Parametri tecnici:

Metodo di stampa:	Termica diretta
Velocità di stampa:	20/ S 0mm
Larghezza del rotolo:	79,5 ± 0,5 millimetri
Diametro di stampa:	Φ80mm
Spessore della carta:	0.06-0.08mm
Capacità della colonna:	576 punti / linea512 Punti / linea
Interlinea :	3,75 millimetri(Regolabile mediante comandi)
Comando di stampa:	Compatibile con il comando ESC / POS
Tipo di interfaccia:	USB+Seriale 25P/ Porta parallela 36P / LAN
CUTters vita:	1 milione di tagli
Pvita della testa di rinta:	100 km
Buffer di input :	2048Kbytes
NV Flash:	256Kbytes
Adattatore di alimentazione:	AC110V / 240V,50 ~ 60 Hz
Alimentazione elettrica:	DC 24V / 2,5A
Fornitura di cassette contanti:	DC 24V / 1A
Ambiente di lavoro:	Temperatura (0~45) umidità (10~80%)(Non- condensare)
Ambiente di lavoro:	Temperatura (0-45) grado centigrado, umidità (10-80%) nn- condensare
Ambiente di archiviazione:	Temperatura (-10~60°C); Humidità (10~90%)
Dimensione del carattere:	ANK,FontA: 1.5 * 3.0mm / FontB:1.1 * 2,1 millimetri
Barcode:	UPC-A / UPC-E / JA(EAN13)/ JAN8(EAN8 / CODE39 / ITF / CODE93 / CODE128/QR Code/ PDF417 (opzioni)
Personaggi:	PC347(Europa standard),katakana,PC850(plurilingue),PC860(portoghese),PC863(Canadian-Francese),PC865(nordico),Europa occidentale,greco,ebraico,Europa dell'est,Ho corso,WPC1252,PC866(Cirillico 2 #),PC852(latin2),PC858,IranII,lettone,Arabo,PT151(1251)
Caratteristiche fisiche:	Peso: 1.25kg; Dimensione dell'aspetto: 190 × 145 × 143mm (lunghezza * larghezza * altezza)

C.Pictures:



80mm Thermal Printer with Auto Cutter

OCPP-80E



Product Picture



Features:

Reliable with good price



Supports black mark detection and order reminding function, compatible with OPOS driver;



Supports multi 1D barcodes and 2D codes printing;



100M Ethernet port, ultra high speed data transmission;

Supports 256KB NV Logo storage
and 2M big buffer memory;



Desktop or wall-mounted
type for option;



Supports printing status monitor
and anti-losing order function.





Restaurant



Supermarket



Pharmacy



Warehouse



Clothing store



Bookstore

Parameter

Printing method:	Direct thermal
Printing speed:	230mm/s、260mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line , 512dots/line
Line's pacing :	3.75mm (Adjustable by commands)
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V、50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0 ~ 45) humidity(10 ~ 80%) (Non- condense)
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10 ~ 60℃); Humidity(10 ~ 90%)
Character size:	ANK, FontA:1.5*3.0mm/ FontB: 1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA (EAN13) /JAN8 (EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、 PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、 Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、 PC858、IranII、Latvian、Arabic、PT151 (1251)
Physical characteristics:	Weight: 1.25Kg; Appearance size: 190×145×143mm (length * width * height)

Supported Languages:

Afrikaans	Arabic (Tunisia)	English (British)	French (Switzerland)	Latvian	Spanish (Costa Rica)
Albanian	Arabic (Yemen)	English (Canada)	German (Austria)	Lithuanian	Spanish (Dominican)
Arabic (Algeria)	Basque	English (Caribbean)	German (Liechtenstein)	Macedonian	Spanish (Ecuador)
Arabic (Bahrain)	Belarus	English (Irish)	German (Luxembourg)	Polish	Spanish (Guatemala)
Arabic (Egypt)	Bulgarian	English (Jamaica)	German (Standard)	Portuguese (Brazil)	Spanish (Mexico)
Arabic (Iran)	Catalan	English (New Zealand)	German (Switzerland)	Portuguese (Portugal)	Spanish (Panama)
Arabic (Jordan)	Chinese (Singapore)	English (South Africa)	Greek	Romanian	Spanish (Paraguay)
Arabic (Kuwait)	Chinese (Hongkong)	English (US)	Hebrew	Russian	Spanish (Peru)
Arabic (Lebanon)	Chinese (PRC)	Estonian	Hun	Serbian	Spanish (Uruguay)
Arabic (Libya)	Chinese (Taiwan)	Faroese	Icelandic	Slovak	Spanish (Venezuela)
Arabic (Morocco)	Croatian	Farsi	Indonesian	Slovenian	Thai Language
Arabic (Oman)	Czech	Finnish	Italian (Switzerland)	Swedish	Turkish
Arabic (Qatar)	Danish and Norwegian	French (Belgium)	Italian	Spanish (Argentina)	Ukrainian
Arabic (Saudi Arabia)	Dutch (Belgium)	French (Canada)	Japanese	Spanish (Bolivia)	Urdu
Arabic (Syria)	Dutch (standard)	French (Luxembourg)	Korean	Spanish (Chile)	Vietnamese
Arabic (UAE)	English (Australia)	French (Standard)	Vietnamese	Spanish (Colombia)	

Power plug for option:



How to use?

Connecting the printer:

- ▶ The power adapter cable connect to the printer power interface
- ▶ The interface cable connect on the printer port behind
- ▶ The cash drawer connecting cable connect to the printer's behind the cash drawer interface



Installation of paper roll:



- Open the printer cover.
- Install the roller in the roll paper, and put them into the printer.
- Pull out some paper outside the printer and then close the printer cover.
- Close the top cover. Press the printer cover to avoid error position of roll paper.
- Tear-off the paper correctly.

Setting the Printing Mode(DIP switches):

The DIP switches are used to set the printer to perform various functions, such as cutter mode, character set, speed, beeper, print density and etc.



Power indicator:
Turn on/off the printer

Alarm indicator:
When the printer is out of paper, the cutter error occurs or printer head overheats, the ALARM indicator flashes.

Paper indicator:
Both of paper indicator and error indicator are on, means paper end-user, both of paper indicator and error indicator are off, means have paper.

FEED button:
Press to feed paper manually.

Clean of printer:

When the printer has the following conditions should clean the print head:

- ❑ The printer does not clear
- ❑ The page frame lengthways of printer has some not clean
- ❑ Paper feed with a large noise

Printer cleaning steps as follows:

- ✓ Shut off the power of printer, Open the Top Cover; If there is paper, please wipe off the paper;
- ✓ If it just finished a printing, please wait for a while until the print head cooling;
- ✓ With a soft cotton cloth dipped in ethanol (to be wrung) erase the thermal printer head thermal surface dust, stains;
- ✓ As the anhydrous ethanol evaporate completely, closed the top cover, and restart to print.

Production Process

No.	Production Process	No.	Production Process	No.	Production Process
1	 Inspection 1	2	 Soldering	3	 Assembling 1
4	 Assembling 2	5	 Function Test	6	 Ageing Test
7	 Inspection 2	8	 Packing 1	9	 Packing 2

Quality Assurance:



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours ageing test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:



Warranty and After Sales:



- ▶ All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- ▶ Spare parts will be provided for mass orders for customers' local maintenance.
- ▶ Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- ▶ Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- ▶ Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- ▶ Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- ▶ 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:



Double wall corrugated board



Double outer cartons

Marks and fragile stickers

Outer protective film



Payment:



secure payment



Aliexpress

PayPal

Trade Assurance

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.



Company Profile



TRADE ASSURANCE

- 100% money refund for Late shipment & Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers , Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Why you choose us?



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: ocom@ocominc.com, info@possolution.com.cn ;

Tel: +86.755.86053207 ext 800;

Fax: +86.755.86053207 ext 868;

QQ: 2485890637, 190852203;

Wechat: szocominc, hj34924238;

Whatsapp: 008613352932860;



D.FAQ:

1. Garanzia

OCOM si impegna a fornire prodotti e servizi economicamente convenienti con la massima qualità in grado di soddisfare le esigenze dei clienti, la nostra garanzia dei prodotti è di circa 12 mesi dalla spedizione normalmente, alcuni modelli designati possono avere fino a 24 mesi di garanzia. Per ordine di massa, possiamo fornirvi alcuni pezzi di ricambio per la riparazione locale. E dopo, è possibile restituire parti guasti per le rilavorazioni.

2. Termini di pagamento

Per ordine di massa, puoi pagare utilizzando T / T, LC, Western Union, Escrow o altri. Circa l'ordine dei campioni, T / T, Western Union, impegno, Paypal sono accettabili. Il servizio di deposito è fornito da Alipay.com. Attualmente, puoi pagare con Moneybookers, Visa, MasterCard e bonifico bancario. Puoi anche pagare con carte di debito selezionate, tra cui Maestro, Solo, Carte Bleue, PostePay, CartaSi, 4B e Euro6000.

3. Spedizione

Accettiamo tutti i tipi di modi di spedizione, tra cui: espresso, aereo, mare, auto, o ritirati personalmente dai clienti.

4. Disponibilità del campione e & Politica

Dopo che i clienti hanno confermato le nostre specifiche, siamo molto lieti di fornire campioni per test e qualifiche. Tutti i campioni devono essere pagati prima della spedizione, e il prezzo dei campioni è leggermente superiore all'ordine di massa. Quando viene effettuato l'ordine di massa, possiamo restituire il costo dei campioni o inviarti altri prodotti con le spedizioni. Puoi acquistare i campioni direttamente da noi usando t / t, western union o paypal. E puoi anche acquistarlo sul nostro negozio online su aliexpress: http://www.aliexpress.com/store/403448?tracelog=minisite_CI L'ordine di campionamento è necessario prima di passare alle nostre factorie

5. Servizio post-vendita:

* Abbiamo la migliore garanzia commerciale dell'1% fino a USD12000 garantiti da alibaba, che può garantire bene i vostri soldi per garantire il lead time e la qualità dei prodotti. (1) Tutti i prodotti di garanzia non è inferiore a un anno, alcuni modelli anche fino a due anni di garanzia. (2) Saranno forniti pezzi di ricambio per gli ordini di massa per la manutenzione locale dei clienti. (3) Hanno distributori o agenti autorizzati nel mercato principale che possono fornire servizi di riparazione e sostituzione locali. (4) La gestione professionale del CRM assicura le richieste e il tracciamento degli ordini dei clienti. (5) Vendite con molti anni di esperienza nel commercio estero, conoscenza delle lingue straniere e forte senso di responsabilità. (6) 7 * 24 ore online, i giorni lavorativi rispondono entro quattro ore, i giorni di riposo entro 12 ore. 6. Scarica

È possibile accedere a <http://www.possolution.com.cn/cn/download.html> driver di download, software SDK, specifiche del prodotto e manuali dell'utente.

7. Guida video

Per aiutare i clienti a utilizzare meglio i nostri prodotti, abbiamo registrato e caricato alcune linee guida video, le puoi trovare su <http://www.possolution.com.cn/video.html>.

8. Politica di MOQ

Nessuna limitazione di MOQ per i prodotti standard, ma il prezzo unitario è diverso. Per la produzione personalizzata, è possibile discutere il MOQ con il nostro rappresentante di vendita.

9. Richiedi un preventivo

Richiedi un preventivo su <http://www.possolution.com.cn/inquiry.html>
E.

Azienda: OCOM è un fornitore leader di prodotti One-Stop POS e Auto-ID correlati qualificato dalla società Global Fortune 500. Abbiamo la garanzia di Trade Assurance di primo livello.

Il portafoglio di prodotti OCOM comprende stampanti termiche, stampanti di codici a barre, stampanti a matrice DOT, scanner di codici a barre, collettore di dati, macchine POS e altre periferiche POS, ampiamente utilizzate per la vendita al dettaglio, ristoranti, banche, lotterie,

trasporti, logistica e altre applicazioni. Abbiamo CE, FCC e altre certificazioni richieste.

Da quando è stato istituito nel giugno 2007, OCOM ha aderito al sistema di qualità ISO9001: 2008. Ci concentriamo sulla qualità dei prodotti affidabili e sul prezzo competitivo. Abbiamo servito più di 1300 clienti in 133 paesi, 40 dei quali sono i maggiori distributori sul loro territorio. I nostri mercati principali sono in Europa, Australia e in rapida crescita in Sud America e Africa. L'elenco dei clienti include famosi Unilever, O2, Equicom ...

La missione di OCOM è quella di essere la scelta convincente per i nostri partner, basata sulle nostre tre convinzioni di base: "Integrità, sforzo per eccellenza, cooperazione vincente", vorremmo stabilire partnership stabili e affidabili con clienti in tutto il mondo. OEM / ODM è il benvenuto.

Insieme cerchiamo il meglio.

F.Contact:

Contatto: Harold Hu

OCOM Technologies Limited

Indirizzo: 4 / F, Block 10, Zhongxing Industrial Park, Chuangye Road, Distretto di Nanshan, Shenzhen 518054, Cina;

Sito Web: www.ocominc.com, www.possolution.com.cn;

E-mail: sales14@ocominc.com;

Skype: [sales14@ocominc.com](https://www.skype.com/people/sales14@ocominc.com)

MSN: ocomsales14@hotmail.com;

Whatsapp: 0086.18948789890;

Wechat: 0086.18948789890;

Cellulare: 0086.18948789890;

QQ: 1467261417;

Tel: 0086.755.86053207-814;

Fax: 0086.755.86053207-868;