

# Pos Machine Touch Screen Android Pos Terminal All in One Pos System with Cash Register

(M/N: POS -H156W/A-H151W/A)



OCOM H Series pos Integrated High Speed Stampante termica e modulo dello scanner ad alta velocità all'interno, è un tipo di macchina conveniente per l'utilizzo, diversi colori del telaio rendono la macchina più bella,

Interfaccia IO estesa Effettuare alcuni dispositivi più esterni collegati, coperchio posteriore appena progettato che può essere facilmente rimosso senza attrezzi per installazione e manutenzione più veloci

## Caratteristiche:

Intel Celeron Series e Intel Core I3 I5 Processore per opzione

Processore RK3288 ad alta velocità RockChip

EMMC 8 GB / 16 GB / 32 GB per opzione

Driver hard msata SSD 64GB, SSD 128GB un 256 GB per opzione

Stampante termica ad alta velocità da 58 mm e 80 mm integrata per opzione

Pannello tattile capacitivo proiettato multi-punto

Lato opzionale MSR e VFD220 visualizzano il display del cliente montato sul coperchio posteriore

Scanner per bar-codici integrato per opzione

Display SureFace TRUE e ACQUA / RESISTENTE RESISTENTE RESISTENTE

## Specifiche:

Modello	POS -H156	POS -H151
Nome	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Housing	plastic with metal combined	
Colore	white machine body or black machine body match orange or blue frame colors	
Schermo		
Schermo principale	15.6 inch touch screen monitor	15.1 inch touch screen monitor
Risoluzione	1366*768	1024*768
Luminosità	250cd/m <sup>2</sup>	
Vista ad angolo	Horizon: 150; Vertical :140	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional	15.1 inch display W/ or W/o touch function, resolution 1024*768
Customer display	2*20 VFD mounted to back cover for option	
prestazione		
Windows J1900	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 <sup>th</sup> generation CPU for option
	Memoria di sistema	1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option
	Dispositivo di archiviazione	Msata SSD 64GB or higer, up to 256GB
	Audio	On board Real Tek ALC662 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
	Sistema operativo	Windows7/8/10, Embedded,WE POS ,Linux
Android RK3288	Motherboard	Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional
	Memoria di sistema	On board DDRIII 2GB,4GB for option
	Dispositivo di archiviazione	On board 16GB EMMC,32GB for option
	Audio	On board Real Tek ALC5640 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Sistema operativo	Android 7.1
Connectivity		
Windows/Android(J1900&RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB *6	
	MIC in*1, Audio out*1	
Windows(J1900)	COM(RS232) *1 or HDMI*1 for option	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 for option	
Android(RK3288)	COM(RS232) *1	
	On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TF card slot*1	
Opzioni		
80mm thermal printer	direct thermal printing	
	100mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 50km	
	LPT communication	
58mm thermal printer	direct thermal printing	
	85mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm	
	thermal head life 50km	
	LPT communication	

MSR	optional side MSR
web camera	web camera mounted on top of the display for option
Scanner	support 1D&2D code-scanning for option
Speaker	4ohm/5w speakers inside for option
Pacchetto	pacchetto
Il peso	net□5.6Kg , gross:7.7Kg for 15.6 with15.6 dual screen /no printer built in
Package with foam inside	340*450*480mm
2in1 carton	700*460*500mm /gross□17Kg
Ambiente	
Temperatura di esercizio	0 to 40 degrees centigrade
Temperatura di conservazione	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%
Accessori	
Adattatore di alimentazione	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A out put adaptor only for W/ 80mm printer machine
Cavo di alimentazione	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Driver della scheda madre e driver touch all'interno per l'opzione
Altro	
Conformità	Segno di classe FCC Classe A / CE / LVD / CCC

## ProdottoPanoramica:

DoppioScreens.genere





POS-H15





POS-H15









POS-H15









POS-H15



Separareschermogenere





POS-H15





POS-H15

