Vinci 8 Compatibile Commercio al dettaglio 2 pollici stampante termica per ricevute
(Modello: OCPP-582)

Specifica:

Metodo di stampa	Termica diretta
Carattere Stampa	FONT A: 33 o 35; FONT B: 40 o 42
Dimensione dei caratteri	Font A: 12 × 24; Font B: 9 × 17; Cinese: 24 X 24
Barcode	JAN13(EAN13)JAN8(EAN8)CODE39
Comando di stampa	compatibile con EPSON ESC / POS
Lingua	Supporto per la lingua compratore
Caratteri per riga	384dots / linea (203DPI)
Velocità di stampa	90 millimetri / sec
Larghezza carta	57.5 ± 0,5 millimetri
Spessore carta	0.06-0.08mm
MCBF (la vita)	50 km
Dimensione	235X145X125mm
Peso lordo	2.6KG
Taglierina automatica	taglierina manuale
Sensor	Carta Near End Sensor, sensore di fine carta, Sensore copertura aperta
Rotolo di carta	φ65mm
Interfaccia	Parallela, USB, LAN
Autista	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / Win 7 / Linux
Alimentazione elettrica	DC12V / 3A

Particolari del prodotto:

Product Picture

Features

Simple but not easy

High speed, long lifetime, high quality, low repair rate, applicable for various software

Modern design, easy to use

Support Logo download printing

GB2312 Chinese Character Library
Support Simplified Chinese/traditional Chinese and various international languages

All-round show

Application Area

Food delivery, restaurant, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Price Tag, Retail/Farm

Parameter

Printing method	Direct thermal
Print font	FONT A: 33 or 35; FONT B: 40 or 42
Character size	Font A : 12 × 24; Font B : 9 × 17; Chinese: 24 X 24
Barcode	JAN13（EAN13）JAN8（EAN8）CODE39
Printing command	compatible with EPSON ESC/POS
Language	Buyer language support
Character per line	384dots/line (203DPI)
Printing speed	90mm/sec
Paper width	57.5±0.5mm
Paper thickness	0.06-0.08mm
MCBF(life)	50km
Dimension	235X145X125mm
Gross weight	2.6KG
Auto cutter	manual cutter
Sensor	Paper Near End Sensor, Paper End Sensor, Cover open
Roll paper	φ65mm
Interface	Parallel, USB, LAN
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Linux

Paper Roll Installation

A Open the printer cover.

B Install the roller in the roll paper, and put them into the printer.

C Pull out some paper outside the printer and then close the printer cover.

D Close the top cover. Press the printer cover to avoid error position of roll paper.

E Tear-off the paper correctly.

Connection



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.