

1. Good di OoOOSsiPUNzione del calore SisTeMa POS laVotare bene in un ambiente più duro
2. Super-Slim tocco SScreen display e design elegante migliora il tuo profilo più alto
3. More scientifico struttura separata per una facile manutenzione e smontaggio

Modello	- 1562-W	- 1562-A
Nome	15. 6 pollice Tocco POS t Erminial	
Alloggio materiale	Allievo e base in lega di alluminio	
ScHermo principale	15. 6 Monitor touch screen pollici , Pannello IPS	
Resolu zione	1920*1080	
Luminosità	22 0cd/m ²	
Visualizzazione a ngle	Orizzonte: 90, Verticale: 60	
Touch s creen	Multi-punto Proiettato GG tocco capacitivo	
Sub- display	Display da 11,6 pollici W/ o w/ o toccare la funzione per l'opzione	
Prestazione		
Scheda madre	Intel Celeron J 6412, 2,0 GHz I ntel core i3 CPU per l'opzione	Serie RockChip RK3 568 , Quad Core 2.0 G
Sistema m Emory	1*So-Dimm DDR 4 slot, Supportoo 3200MHz, 4GB /8 GB /16G per opzione	A bordo di DDR4 4GB, 8G per l'opzione
Dispositivo di archiviazione	64 GB M.2 SSD o HIG h ehm, fino a 512 GB	A bordo di 32 GB EMMC 64 GB per l'opzione
Lan /Wlan	10/100 /1000 MBS, Realtek RTL8111F LAN CHIP Incorporato in mini slot PCI-E, supporto WiFi incorporato supporto	10/100 /1000 MBS, Realtek RTL8111F LAN CHIP Support Wi-Fi 802.11 UN/ b/g/n , BT3.0/BT4.0
Operativo s ystem	Finestre 1 0 /11	Android 11
ConNettatività		
Esterno I /O port J 6412	P Ower pulsante*1	
	12V DC in Jack*1	
	LAN: RJ-45*1 , USB*6, com*2, mini hdmi*1	
	Allinea e microfono in 2in1 jack *1	
Esterno Porta I/O RK3568	P ower pulsante*1	
	12V DC in jack*1	
	LAN: RJ-45*1 , USB*6, com*1	
	Allineate*1	
Ambiente		
Temperatura operativa	0 a 5 0 gradi centigradi	
Temperatura di conservazione	- 2 0 a 60 gradi centigradi	
Umidità funzionante	10%~ 9 0% Nessuna condensa	
Umidità di conservazione	10%~ 90% Nessuna condensa	
Pacchetto		
Peso	Net Peso 3.6K g , g Ross peso 4.9k g	
Pacchetto con schiuma all'interno	430*240 * 370 mm per uno schermo singolo	
Accessori		

Adattatore di potenza	110-240 V/50-60Hz AC Potenza i nput , DC12 V /5a adattatore di output
Cavo di alimentazione	Perca del cavo di alimentazione compatibile con USA / UE / UK ecc.



Super Slim Die-cast Aluminum Touch POS Terminal

Model: POS-1562



Super Slim



Die-cast Aluminum



Waterproof



Windows/Android



10mm Ultra-thin Body

High-end titanium gray color.
Modern stylish, industry new innovation.




Full Die-cast Aluminum Body

Uniform and delicate oxidized color,
more advanced than the painting process.



Full Lamination Advantage

Improved light transmittance ensure
high-definition display and higher
brightness to compatible with outdoor use.
Dust-free makes the screen cleaner.



Waterproof

Improved waterproof performance of the
surface, to avoid accidental water ingress.



High-Efficiency

Configured DDR4 3200MHz RAM and NVME
protocol M.2 SSD, faster response when operate.



Scientific Structural Design

Mainboard is sticked behind of lcd screen
ensuring maintenance convenient and
well-done cables management.



Specifications



OS
Windows 10/11
Android 11



Processor
Intel Celeron J6412
Rockchip RK3568



Memory
DDR4 4GB/8GB/16GB



Storage device
128G/256G/512G SSD
32G/64G/128G eMMC



Main screen
15.6" LCD (1920*1080)
16:9, Multi-point projected G+G capacitive touch



Sub-display
11.6"
Touch function for option



Interface
USB2.0*4, USB3.2*2, RJ48(Serial)*2,
1000Mbps LAN*1, Mini HDMI*1,
12V 5A DC input*1, Audio*1



Housing material
Aluminium alloy
Titanium grey



Options
3W Speaker
Wifi&Bluetooth
4G LTE



Environment
Operating temperature: 0°C - 50°C
Storage temperature: -20°C - 60°C



Size (W*H*D)
Product size: 370*180*296(mm)
Packaging size: 430*240*390(mm)



Weight
Net: 3.55kg
Gross: 4.9kg

Notice: Product specifications subject to change without prior notice. Product pictures are taken with engineering sample. OCOM reserves the right to change the product information without prior notice.

Website: www.ocominc.com









