

DireCTe tHerMische / thermische overdracht Bar Printer van codelabel

Funcities:

Directe thermische / thermische overdracht Afdrukken

200 m H Z 32-bit RISC-Verwerker

8 MB Sdram -x-8 MB Flash -geheugen

Dual-Motor Gear Driven Design

1 52 m M (6 ")))) Inches per secopde printsnelheid (Mbijl)

300 meter (984 ") Linttoevoer op een 25.4 m M (1 ") kern

203 DPI of 300DPI -Resolutie voor optie

High-einde Japanse ROHM -printerkop, het drukleven is van plan 100 km

steun Gapsensor , Open het dekselsensor , Zwarte mark -sensor , Lintsensor

Biedt gratis bartender Labelbewerkingssoftware

Zelf ontwikkelde gratis bewerkingssoftware Steun I Os/ Android / Harmonie OS / Ramen / Mac, vijf - terminale interoperabele

Specificatie

Model	OCBP-T4202	OCBP-T4302
Kleur	Zwart	
Processor	32bit CPU	
Optionele interface	USB2.0 (standaard)/USBBT/USBBTWIFI/USBLAN	
Echt t ime c slot	Standaard	
Printertaal	TSPL	
Printer Hoofdleven	100 km	
Stroomvoorziening	I nut : AC 100V-240V, 50-60Hz , Uitvoer : DC 24V / 2.5 A	
Sensoren	Gap -sensor, Cover Opening Sensor , Zwarte mark - sensor , Lintje end sensor	
Geheugen	8MB Flash Memory/8MB Sdram/Flash -geheugen	
Accessoires	Quick Start Guide , USB -kabel , Netsnoer , Label spindel Externe universele schakelvoeding , Tablijf x 2, 1,5 "kernadapter x 2, Lint spindel x 2, Lintpapierkern	
software	Bestuurder: Windows/Mac SDK: Windows/Android/iOS	
Afdrukmethode	Thermische overdracht / direct thermisch	
Resolut i on	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Max. afdruksnelheid	1 52 mm (6 ") /S	1 27 mm (5 ") /S
Max. afdrukbreedte	10 4 mm (4. 09 ")	104 mm (4. 09 ")

Max. printlengte	1778 mm (70 ")	889 mm (35 ")
Grafische afdrukken	Bimap, BMP, PCX (max. 256 kleuren)	
Barcode	1d barcode: Code 39, Code 93, Code 128ucc, Code 128, Subsets A, B, C, Codabar, Interleaved 2 van 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN en UPC 2 (5) Digits Add-On, MSI, Plessey, POSTNET, China POST, GS1 Databar, code 11 2d barcode: PDF-417, Maxicode, Datamatrix, QR-code, Aztec	
Interne lettertypen	8 Alpha-Numeric Bitmap-lettertypen, Windows-lettertypen zijn te downloaden van software.	
Lettertype en streepjescode rotatie	0 ° , 90 ° , 180 ° , 270 °	
Grafisch	BIMAP, BMP, PCX (max. 256 kleuren)	
Media		
Type media	Continu, Die-Cut, Black Mark, Fan-Fold, Gotched (Buiten Wond)	
Mediabreedte	20-112 mm (0,78 "-4,4")	
Mediadikte	0.06 ~ 0. 254 mm (2.36 ~ 10 Mil)	
Etiket lengte	10 ~ 1178 mm (0. 39 " ~ 7 ")	10 ~ 889 mm (0. 39 " ~ 35 ")
Labelrolcapaciteit	127 mm (5 ") OD (externe diameter)	
Lintje capaciteit	300 meter lang M ax	
Lintbreedte	110 mm	
Lintkern binnendiameter	25,4 mm (1 ")	
Fysiek		
Dimensie	2 80 mm *2 10 mm *1 70 mm	
Gewicht	Netto: 2,25 kg bruto: 3,25 kg	
Pakketdoos	370*240*205mm	
4 op 1 doos	500*390*430 mm/14,5 kg	
Omgeving		
Werk temperatuur & vochtigheid	0 tot 4 5 graden Celsius , 10%~ 80% Geen condensatie	
Opslag temperatuur & vochtigheid	-20 tot 60 graden Celsius , 10%~ 90% Geen condensatie	

Thermal Transfer Label Printer

Versatility Creates Efficiency

- Thermal Direct Labels
- Thermal Transfer Labels
- PET Silver Labels
- Garment Hang Tags
- Wash Care Labels



Dual Printing Mode

Direct Thermal Print / Thermal Transfer Print

Switch at Ease Between Both Modes

Direct Thermal Mode

MODE 1



Direct
Thermal
Labels

No TTR Ribbons Required

Thermal Transfer Mode

MODE 2



Thermal Transfer Labels

PET Silver Labels

Garment Hang Tags

Wash Care Labels

TTR Ribbons Required

Versatile Sizes Compatible Adjustable Media Guide

Different Sizes Printed by Guide Width Adjusted Flexibly



Professional and Durable Print Head

High-resolution Printing at Lightning Speeds

203dpi Printing Speed

152^{Max.}mm/s



Ordinary Print Head

Durability

Professional Print Head

Durability

Various Connectivity

Multiple OS Compatible

Running smoothly with
Windows XP, 7, 8, 10, 11 and Mac OS

USB Connectivity

- ✓ Windows PC
- ✓ Mac

Also compatible with Google Chrome OS after installing the plugin in the Google browser.

Bluetooth Connectivity

For Bluetooth Version Only

- ✓ Windows Laptop
- ✓ Android Phone
- ✓ iPhone
- ✗ Mac

WiFi Connectivity

For WiFi Version Only

- ✓ Windows PC
- ✓ Mac
- ✓ Android Phone
- ✓ iPhone

Ethernet Connectivity

For Ethernet Version Only

- ✓ Windows PC
- ✓ Mac

Widely Applicable Supporting Various Labels



Direct Thermal Labels



PET Silver Labels



Garment Hang Tags



Thermal Transfer Labels



Wash Care Labels



Price Tags



Different Resolution for Option

For Different Printing Needs



For Most Printing Needs



For Fine Text Printing Needs

Resolution	203dpi	300dpi
Label Material	Direct Thermal Labels, Thermal Transfer Labels, PET Silver Labels, Synthetic PP Labels, Garment Hang Tags, Wash Care Labels	
TTR Ribbons	Wax Ribbon, Wax-resin Ribbons, Resin Ribbons, Washable Resin Ribbons	
Available Version	USB / Bluetooth / WiFi / Ethernet	
Media Type	Continuous paper, gap paper, folded paper, black mark paper, hole-punched paper	
Printer Dimension	280×220×168mm(L×W×H)	
Print Width	15-104mm	15-108mm
Print Speed	152mm/s	127mm/s

Default Accessories List



①



②



③



④



⑤



⑥



⑦



⑧



⑨

- ① User Guide ② USB Cable ③ Power Adapter ④ Power Cord
- ⑤ Media Shaft & Baffle Plate x 2 ⑥ Ribbon Shaft x 2
- ⑦ Ribbon Rewind Paper Core ⑧ Ribbon Sample Roll
- ⑨ Label Sample Roll