

Handheld Android pos-betaalterminal met thermische printer

(M / N: POS -Z90)

Voorzien zijn van:

- 1 Android 5.1-besturingssysteem
- 1 5.0 inch schermaanraking
- 1 Lange stand-by batterijcapaciteit is 3600 mAh
- 1 58 mm thermische printer
- 1 5 miljoen pixels camera
- 1 2G / 3G / 4G wifi, bluetooth-communicatie,
- 1 Geïntegreerde magnetische kaartlezer, inductie IC-kaartlezer en contact-IC-kaartlezer
- 1 Geslaagd voor EMV L1 L2 en PBOC-bankbetalingscertificering
- 1 Thecradle kan worden gebruikt voor communicatie, opladen, powerbank en draadloos netwerk (optioneel)

Toepassing:

Applychain supermarkten, restaurants, buurtwinkels, kledingwinkel, gebouwen, bakkerij, kassamedewerker, betalen, gaat verkopen, spaart de bedrijfsbeheerfunctie.

Technische specificatie:

| Basis informatie | |
|--------------------------|--|
| Besturingssysteem | Android 5.1 |
| RAM | RAM: 1 GB |
| Uitgebreid opgeslagen | FLITS: 8 GB |
| Scherf weergeven | 5,0 duim |
| Touch screen | Capacitief touchscreen, ondersteuning van de elektronische handtekening |
| Accu | Lithiumbatterij 3600 mAh, 3,7 V. |
| Bluetooth | Bluetooth 4.0 |
| Camera | 5 megapixel camera |
| Pos itioning-functie | GPS AGPS WLAN voor Pos-itioning |
| Printer | 58 mm thermische printer 30 mm diameter papierrol |
| Koppel | Micro USB |
| POS-functie | |
| Magnetische kaartlezer | Magnetische kaartlezer met volledige track Ondersteuning van ISO1788 / 7812, AAMVA-protocol |
| IC-kaart lezen-schrijven | Ondersteuning van het ISO7816-protocol |
| Contactloze kaartlezer | Ondersteuning van ISO / IEC 14443 Type A&B, Mifare, felica kaart, in lijn met de EMV / PBOC PAYPASS specificatie |
| PSAM-kaart | Bankbeveiliging betaling chipkaart |

| | |
|-------------------------------|---|
| Certificatie | Unionpay kaartacceptatie terminal netwerk detectie EMV / PBOC3.0 L1 en L2 certificering EMV / qPBOC3.0 L1- en L2-certificering Unionpay intelligente veiligheidsnormen point-of-saleterminals |
| Netwerkparameters | |
| Netwerktipe | GSM, WCDMA, TD-SCDMA, FDD-LET, TDD-LTE |
| Netwerkspectrum | GSM850 / 900/1800/1900 |
| | WCDMA2100 / 1900/900/850 |
| | TD-SCDMA B34 / B39 |
| | FDD-LTE B1 / B2 / B3 / B4 / B5 / B7 / B8 / B20 |
| TDD-LTE B38 / B39 / B40 / B41 | |
| WLAN | IEEE802.11.b / n / g |
| Fysieke parameters | |
| Grootte | 191 mm × 80 mm × 46 mm |
| Gewicht | 650 g |
| Operationele Temp | -20 ° C ~ 60 ° C |
| Opslagtemperaturen | -40 ° C ~ 80 ° C |
| Vochtigheid | 10% ~ 90% RH niet-condenserend |

Foto's:

Model: POS-Z90

Handheld Payment POS Terminal

OCOM POS-Z90



Printing



Scanning



NFC



Card Reader



Battery

Android 5.1 operating system;
 Quad core Qualcomm MSM8909;
 5.0 inch touch screen;
 Long standby battery capacity is 2800mAh;
 58mm thermal receipt printer;
 5 million pixels camera;
 2G /3G/4G Wifi, Bluetooth communication;
 Optional fingerprint reader;
 Integrated magnetic card reader, induction IC card reader and contact IC card reader;
 Passed the EMV L1 L2, PCI and PBOC bank payment certification.





- | | | | | |
|--|--|---|--|---|
| OS OS Android 5.1 | CPU Quad core Qualcomm MSM8909 | Memory 1G RAM+ 8G ROM | Button Power Button | Adapter 5VDC, 2A |
| Wi-Fi IEEE802.11.b/n/g | Bluetooth Bluetooth 4.0 | Size 191*80*46mm | Port 1*Micro USB 1*Mini USB for factory 1*Headset jack | Thermal Printing Paper With: 58mm(Manual cutter) Paper Roll Diameter: 30mm Printing Speed: 70mm/s |
| Card reader IC card read-write *1 Magnetic card reader *1 Non-contact card reader *1 | Camera 5 mega-pixel camera can scan 1D/2D barcode | Micro SD(TF) TF Solt *1 SAM Solt *1 SIM Solt *2 (Standard) | Environment Working temperature: -20 °C ~ 60 °C Storage temperature: -40 °C ~ 80 °C | Display 5.0 Inch Capacitive touch screen support the electronic signature Resolution: 1280*720 |

Optional

-  Cradle
-  Fingerprint reader

Note:

1. Real memory will be reduced due to a number of factors, and there are differences. Operating system also occupy part of memory.
2. Actual product specifications when sold take precedence over what may be listed at this catalogue; Product specifications are subject to change without prior notice.











