

# China Factory High Quality Portable Wireless Memory Scanner

## Features:

China Factory High Quality Portable Wireless Memory Scanner

Integrated non-volatile memory;

32bit decoder;

Data transmission distance reaches 200m in open area;

One receiver can works with 100 scanners without mutual interference;

750mA lithium-ion battery ensures long working hour.

## SPECIFICATIONS:

PHYSICAL CHARACTERSTICS	
<b>Light Source:</b>	Visible Laser Diode (VLD) @ 650 nm
<b>Scanner Dimensions :</b>	168mm * 72mm * 93mm(W * H * D)
<b>Receiver Dimensions:</b>	130mm*45mm*129mm(W * H * D)
<b>Material:</b>	ABS+TPR /Aluminium alloy
<b>Weight:</b>	370g
<b>Scanning Mode:</b>	Hand-held; Continuous Scanning Mode.
<b>Indicator Light:</b>	LED Red and Blue
<b>Buzzer:</b>	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
<b>Width of Scan Field:</b>	60mm@30mm□From engine face□ 98mm@100mm□from engine face□
<b>Depth of Scan Field:</b>	10-450mm□Contrast 0.9 Density 0.25□
<b>Scan Speed:</b>	150 scans/sec
<b>Scan Precision:</b>	0.10-0.825mm
<b>Bit Error Rate:</b>	1/(5million)
<b>Decode Capability:</b>	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
<b>Battery:</b>	3.7V/750mAh,Li-ion
<b>Charge Time:</b>	3.0 Hours
<b>Scan Time:</b>	30 Hours
<b>Current:</b>	95mA (working); 25mA(standby)
<b>Angles:</b>	Pitch:60°; Tilt: 45°
<b>Working Frequency:</b>	433MHz
<b>Communication Distance:</b>	200m□Open Places□
<b>Communication Interface:</b>	USB
USER ENVIRONMENT CHARACTERSTICS	

<b>Temperature:</b>	-10degree Cto 45degree C (Operating), -40degree Cto 60degree C (Storage)
<b>Relative Humidity:</b>	5%-90%(Non-Condensing)
<b>Drop Specification:</b>	Withstands repeated 1.5m drops to concrete surface
<b>Ambient Illumination:</b>	0~100,000 LUX
<b>Electrostatic Discharge:</b>	Conforms to $\pm 12$ KV air discharge and $\pm 6$ KV of contact discharge
<b>Safety Certificate:</b>	CE, FCC, Class 2, RoHS

**Product Details:**



**Relevant documents:**

Do you want to know more product information?Please Click here.

[Specification](#)

[User's Manual](#)