

Mini usb laser barcode scanner

(OCBS-LA11)

Feature:

- ✘ 1. Handheld laser barcodescanner met automatische sense functie;
2. Flexible operatie met 360 gradenrotatie metalen standaard;
3. high scansnelheid (100 scans / sec) en lange leesafstand;
4. Excellent decoderen capaciteit;
5. KBW, RS232 en USB ondersteund;
6. Grey en zwarte kleur beschikbaar

Specificatie:

Prestatie Karakteristieken	
Licht Bron:	Zichtbaar laser (650-670nm)
Scannen Rate:	100 scans per seconde
Lectuur Afstand	2.5 ~ 600mm (100% UPC / EAN)
Type scanner:	Bi-directionele
Resolutie:	0.10mm (4mil) bij PCS 0.9
Print Contrast Minimum:	30%, ten minste reflecterende verschil (@ 650nm)
Error Rate:	1/3000000
Decode Capability:	UPC / EAN, UPC / EAN met supplementals, UCC / EAN128, code 39, code 39 volledige ASCII, code 39 Trioptic, code 128, code 128 volledige ASCII, Codabar, Interleaved 2 of 5, discrete 2 van 5, code 93, MSI, code 11, ATA, RSS-varianten, de Chinese 2 van 5 ...
Lichamelijk Karakteristieken	
Interfaces Ondersteunde:	PS2, RS232, USB
Voltage:	DC + 5V +/- 5%
Actueel:	100 mA
Idle Current:	& lt; 40 mA
Energiebron:	Host macht of externe (RS232) voeding
Scannen Hoek	Inclinatie 45 ° Hoogte 60 °
Afmetingen:	L165mm X W63mm X H87mm
Gewicht:	129g (zonder voet)
Staan	Facultatief
Kleur:	Grijs en zwart
Gebruiker Milieu	
Operating Temperatuur:	0 °C ~ 40 °C
Opslagruimte Temperatuur:	-40 °C ~ 60 °C
Vochtigheid:	5 ~ 95% relatieve vochtigheid, zonder condensatie
Elektrostatische Ontlading:	Bevestigen om +/- 15KV luchtafvoer en +/- 8 KV van contactontlading
Drop Specificaties:	Bestand tegen meerdere 1.5m druppels op beton
Veilig:	
EMI / RFI:	FCC klasse A en CE
Laser Safety:	CDRH klasse 2 laser product



Handheld Laser Barcode Scanner

OCBS-LA11



Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with auto sense function;



 Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.

