

Auto Sense Handheld Laser Barcodescanner met standaard
(Model: OCBS - L012)

SPECIFICATIES:

Prestatiekenmerken	
Lichtbron:	Zichtbare laser (650-670nm)
Scan Rate:	100 scans per seconde
Afstand aflezen	2.5 ~ 600mm (100% UPC / EAN)
Scannertype:	Bi-directionele
Resolutie:	0,10 mm (4 mil) bij PCS 0.9
Contrastminimum afdrukken:	30%, minimaal reflecterend verschil (@ 650nm)
Foutpercentage:	1/3000000
Decodeervermogen:	UPC / EAN, UPC / EAN met supplementen, UCC / EAN128, code 39, code 39 volledige ASCII, code 39 trioptic, code 128, code 128 volledige ASCII, codabar, interleaved 2 van 5, discrete 2 van 5, code 93, MSI , code 11, ATA, RSS-varianten, Chinees 2 van 5 ...
Fysieke eigenschappen	
Ondersteunde interfaces:	PS2, RS232, USB
Spanning:	DC + 5V +/- 5%
Actueel:	100 mA
Inactieve stroom:	& lt; 40 mA
Krachtbron:	Hostvermogen of externe (RS232) voeding
Scanning Angle	Helling 45 ° Hoogte 60 °
Dimensies:	L165mm X B63mm X H87mm
Gewicht:	129 g (zonder standaard)
Stand	facultatief
Kleur:	Grijs en zwart
Gebruikersomgeving	
Bedrijfstemperatuur:	0 °C ~ 40 °C
Bewaar temperatuur:	-40 °C ~ 60 °C
Vochtigheid:	5 ~ 95% relatieve vochtigheid, niet-condenserend
Elektrostatiche ontlading:	Bevestig aan +/- 15KV luchtontlading en +/- 8KV aan contactontlading
Drop specificaties:	Bestand tegen meerdere druppels van 1,5 m tot beton
Veilig:	
EMI / RFI:	FCC Klasse A en CE
Laserveiligheid:	CDRH klasse 2 laserproduct

Productdetails:



ocom
All your side

*Handheld Laser
Barcode Scanner*

OCBS-L012

||| Product Picture





Features

Simple but not easy

Handheld laser barcode scanner



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined



with future-proofing;



Grey and Black Color available

All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V±-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive

2. By sea: around 2-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.





Monica Fu



OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: www.ocominc.com

E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn

Skype: [ocomsales01](https://www.skype.com/user/ocomsales01); MSN: ocomsales01@hotmail.com

Ali TM: [cn1001868228](https://www.ali.com/item/cn1001868228); QQ: 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products

Relevante documenten:

Wilt u meer informatie over producten weten?ormatie?alsjeblijft Klik hier.

Specificatie

Handleiding