

# Handheld 1D Laser Bar Code Reader Barcode Scanner

(Model No.: OCBS -L017)

## Funcctie:

200MM/S Scan Speed;  
10-40cm long depth of field;  
Compatible with multiple language layout;  
1.5m free fall on concrete surface;  
Can switch to manual,continuous scanning.

## Specificatie:

Algemeen	
Model	OCBS -L017
Materiaal	ABS+PVC+PC
Taal	meerdere talen
Koppel	USB
Trigger Mode	Manual , Continuous scanning
Operating Current	50mEEN(Operating), 40mEEN(Stand By), 100mEEN(Max)
Stroomvoorziening	DC 5V±5%
Quiescent Current	20mA
ESD Protection	15KV air discharge
Schokbestendig	1.5m free fall on concrete surface
Uitvoering	
Scan Speed	200 scans per second
Scanning Depth	2—9cm(0.1mm Width), 3—30cm(0.3mm Width)
Width of Scan	Min 0.1mm(4mils)
Print contrast	≥25%
Scanning Distance	10-400mm Roll 60°, Pitch45°
Lichtbron	zichtbaar laser 650nm
Decode Capability	1D□UPC-A,,UPC-E,,EAN-8,,EAN-13,,Code 128,, Code 39,,Code 93,, Interleaved 2 of 5,,Matrix 2 of 5,,Industrial 2 of 5, Standard 2 of 5(IATA25) ,Codabar□NW-7□,,enzovoort.
Fysiek	
Casing Size	150mm * 70mm * 95mm
Omgeving	
Working temperatuur-& vochtigheid	0 to 45 degrees centigrade, 10%~80% No condensation
Opslag temperatuur-& vochtigheid	-20 to 60 degrees centigrade , 10%~90% No condensation

