

Omni-Directional 2D Barcode Scanner

(M/N: OCBS -T214)



Funcities:

Large reading window

Quickly identify the screen 1D/2D code

Non-slip drop design

Sound can be adjustable

Specificatie

Algemeen	
Model	OCBS -T214
Koppel	USB
Werkspanning	5V
Starting Curent	380mA
Work Current	240mA
Standby Current	190mA
Shock specification	8 G r.m.s., from 10 to 500 Hz, 2 hours per axis, 3 axes

Uitvoering	
Sensor	Overall exposure CMOS sensor
Lichtbron	Warm yellow LED
Field view	44° (H), 34°(V)
Motion tolerance	> 0.4m/S
Scan Angle	Pitch $\pm 65^{\circ}$ @ 0°Roll and 0° Skew Roll 360°@ 0°Pitch and 0° Skew Skew $\pm 65^{\circ}$ @ 0°Roll and 0° Pitch
Symbol Contrast	20% minimum reflective difference
Ambient Light Immunity	0-100,000 Lux
Typical Depth of Field	Code39(5mil):0mm-120mm,Code39(13mil):0mm-240mm QR(20mil):0mm-210mm Alipay (QR 3*3CM):40mm-650mm Wechat pay(QR 2.3*2.3CM):20mm-550mm
Decoding ability	1D:Code128/EAN128,EAN.UCCcom pos ite, Interleaved2of 5,RSS, Pos tnet,Plessey code,Code 39,Codabar,Code 93, Code 11,Telepen,MSIcode,Standard 2 of 5,UPC/EAN etc 2D:PDF417, QR code, Matrix 2 of 5, MicroPDF417, Australian Pos t, Canada Pos t,Japan Pos t, MaxiCode, Codablock, Aztec, Dutch Pos t, TLC 39,DataMatrix, etc
Fysiek	
Gewicht	Gross:437g
Pakket	151*142*84mm
Omgeving	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation











