

Hoge kwaliteit 433 MHz of Bluetooth Wireless QR Code 2D barcodescanner met stand

Model: OCBS-W231-4/B

Kenmerken:

- 1, 433 MHz draadloze communicatie afstand 300 m outdoor, indoor 100 m; De afstand tot de Bluetooth draadloze buiten 20 m en 10 m overdekt;
- 2, uitgerust met opladen en communicatie
- 3, een zachte plastic cover ter bescherming van de lens en een overzicht aanzienlijk verbetert de prestaties van anti-drop;
- 4, bar codes op het scherm van computers en mobiele telefoons kunnen worden gescand;
- 5, hoeft u geen stuurprogramma's plug & play;
- 6, kunt opslaan meer dan 10.000 stukken van gegevens;
- 7, veelvoudig scanner kunnen worden aangesloten op één ontvanger (433 MHz).

Parameters:

Hebben een lichtbron	617 nm LED
Lichtbron verlichting	625 nm LED
Scannen van hoek	39 ° (H) 25 ° (V)
De hoek van de rotatie	0-360 °
Elevatie-hoek	65 °
Tilt hoek	60 °
Contrast afdrukken	Meer dan 25%
1 d	UPC/EAN, UPC/EAN met supplementals, BooklandEAN, ISSN, UCC coupon uitgebreid gratis Code128, GS1-128, ISBT 128, Code 39, code 39 volledige ASCII-, Code 39 Trioptic, code 93, code 32, Code11, Matrix 2 5 Interleaved 2 van 5, discrete 2 5, Codabar, MSI, 2, 5, Barvariants gegevens, GS1, Korean 3 5, ISBT Concat
2D	Type PDF417, MicroPDF417, complexe codes, TLC-39, DataMatrix, Maxicode en QR code, Azteekse, MicroQR
Interface	USB (kabel Wireless ontvanger)
Communicatiebereik	433 MHz: binnen: 100 m; Buiten: 300 m (max.) Bluetooth: Binnenkant: 10 m; Buiten faciliteiten: 20 m (max.)
Bedrijfstemperatuur	-10 graden C - 45 graden C
Temperatuur bij opslag	-20 ° C - 65 ° C
Luchtvochtigheid bij gebruik	5-85%
Vochtgehalte tijdens opslag	5% - 95%
De duurzaamheid van de	Een verscheidenheid van 1.5 m tot beton kan weerstaan
Ingangsvermogen	5 v DC, 280mA
Oplaadtijd	6 h
Batterij	1500mAh
Luminantie	Interieur: 3.000 LUX max; Zonlicht: max 86000 LUX
IP-graad	Ip42
DECODEREN VAN BEREIKEN	

Een typische uitvoering *		Typische operationele bereiken	
		Focus bereik HD	
Barcode type	De dichtheid van de symbolen	In de buurt van	Veel
De code 39	5.0 mijl	5 mm	90 mm
100% van de UPCA BARCODES	13.0 mijl	8 mm	200 mm
De code 39	20,0 mijl	8 mm	250 mm
PDF 417	6.8 mijl	5 mm	95 mm
De Data-Matrix	10.0 mijl	5 mm	110 mm
QR-code voor	20,0 mijl	10 mm	150 mm
Resolutie 1 d-code 39	4 mil		
De resolutie van de 2D Data Matrix	10 mil		
Materiaal	ABS + PC		
Een dimensie	Scanner (70 * 95 * 168 mm) Base (145 * 112 * 74 mm)		
Netto gewicht	Scanner 185 g Base 186 g		
Bestelinformatie:	OCBS-W231-4: 2D barcodescanner draadloze 433 MHz van de wieg		
	OCBS-W231-B: 2D scanner met barocde Bluetooth cradle		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT
INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

ocominc.com

ocominc