

OCPP-802 80mm Impact thermische printers voor POS-systeem (Model: OCPP-802)

Specificatie:

Afdrukmethode	direct thermisch
lettergrootte	ANK, FontA: 12 * 24dots, FontB: 9 * 17dots
De kolomcapaciteit	576dots / lijn of 512dots / line
Karakterset	PC347 (Standard Europe)Katakana, PC850(Meertalig)PC860(Portugees) PC863(Canadees-Frans)PC865(Nordic) West-Europa,Grieks,Hebreeuws,Oost Europa,Iran,WPC1252,PC866(Cyrrilisch # 2) PC852(latin2)PC858,IranII,Lets,Arabisch,PT151(1251)
Barcode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / Code93 / CODE128
afdruksnelheid	230mm / sec
ontvang buffer	128k bytes
NV flash buffer	256K bytes
papierbreedte	79,5 ± 0,5 mm
MCBF (levens)	100km
commando Printing	Compatibel met ESC / POS
Kassalade controle	DC 12-24V / 1A
papierdikte	0.06-0.08mm
Snijder	Manual Cutter
papierrol	79,5 ± 0,5 mm * φ83mm
Interface	Seriële / parallelle / USB / LAN
Bestuurder	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / win 7 / Linux
Stroomvoorziening	DC24V / 2.5A
Power adapter ingang	AC 110V / 220V, 50 ~ 60 Hz; output:DC 24V / 2.5A
Dimensie	190x145x150mm
Gewicht	3.5kg

Productdetails:

