

# OCP-802 Goedkope USB Thermal kassabonprinter In China (Model: OCPP-802)

## Specificatie:

|                      |                                                                                                                                                                                                                                                  |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Afdrukmethode        | direct thermisch                                                                                                                                                                                                                                 |
| lettergrootte        | ANK, FontA: 12 * 24dots, FontB: 9 * 17dots                                                                                                                                                                                                       |
| De kolomcapaciteit   | 576dots / lijn of 512dots / line                                                                                                                                                                                                                 |
| Karakterset          | PC347 (Standard Europe)Katakana,<br>PC850(Meertalig)PC860(Portugees)<br>PC863(Canadees-Frans)PC865(Nordic)<br>West-Europa,Grieks,Hebreeuws,Oost Europa,Iran,WPC1252,PC866(Cyrrilisch # 2)<br>PC852(latin2)PC858,IranII,Lets,Arabisch,PT151(1251) |
| Barcode              | UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39<br>/ Code93 / CODE128                                                                                                                                                       |
| afdruksnelheid       | 230mm / sec                                                                                                                                                                                                                                      |
| ontvang buffer       | 128k bytes                                                                                                                                                                                                                                       |
| NV flash buffer      | 256K bytes                                                                                                                                                                                                                                       |
| papierbreedte        | 79,5 ± 0,5 mm                                                                                                                                                                                                                                    |
| MCBF (levens)        | 100km                                                                                                                                                                                                                                            |
| commando Printing    | Compatibel met ESC / POS                                                                                                                                                                                                                         |
| Kassalade controle   | DC 12-24V / 1A                                                                                                                                                                                                                                   |
| papierdikte          | 0.06-0.08mm                                                                                                                                                                                                                                      |
| Snijder              | Manual Cutter                                                                                                                                                                                                                                    |
| papierrol            | 79,5 ± 0,5 mm * φ83mm                                                                                                                                                                                                                            |
| Interface            | Seriële / parallelle / USB / LAN                                                                                                                                                                                                                 |
| Bestuurder           | Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP /<br>Win Vista / win 7 / Linux                                                                                                                                                           |
| Stroomvoorziening    | DC24V / 2.5A                                                                                                                                                                                                                                     |
| Power adapter ingang | AC 110V / 220V, 50 ~ 60 Hz; output:DC 24V / 2.5A                                                                                                                                                                                                 |
| Dimensie             | 190x145x150mm                                                                                                                                                                                                                                    |
| Gewicht              | 3.5kg                                                                                                                                                                                                                                            |

## Productdetails:

