

OCP-804 Desktop Thermische Ontvangst Printer met USB-Serial parallele poort (Model: OCP-804)

Specificatie:

Afdrukmethode	direct thermisch
lettergrootte	ANK, FontA: 12 * 24dots, FontB: 9 * 17dots
Column capaciteit:	576dots / lijn of 512dots / line
Karakterset	PC347 (Standard Europe), Katakana, PC850 (meertalige), PC860 (Portugees), PC863 (Canadees-Frans), PC865 (Nordic), West-Europa, Grieks, Hebreeuws, Oost-Europa, Iran, WPC1252, PC866 (Cyrillisch # 2) , PC852 (Latin2), PC858, IranII, Lets, Arabisch, PT151 (1251)
Barcode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / Code93 / CODE128, QR code
afdruksnelheid	260mm / sec
ontvang buffer	64k bytes
NV Flash	128k bytes
papierbreedte	79,5 ± 0,5 mm
MCBF (levens)	100km
commando Printing	Compatibel met ESC / POS
Kassalade controle	DC 12-24V / 1A
papierdikte	0.06-0.08mm
Snijder	Auto Cutter
papierrol	79,5 ± 0,5 mm * ø83mm
Interface	Seriële / parallele / USB
Bestuurder	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / win 7 / Linux
Stroomvoorziening	DC24V / 2.5A
Power adapter ingang	AC 110V / 220V, 50 ~ 60 Hz; Output: DC 24V / 2.5A
Dimensie	200x145x137mm
Netto gewicht	1.56kg

Productdetails:

