

80MM thermische printer

(Modelnummer: OCPP -80M)

Kenmerken:

Hoge snelheid afdrukken van 260 mm / sec

Auto Cutter Life: 1 miljoen sneden

Ondersteuning QR CODE afdrukken

Seriële + USB + LAN-interfaces

Ondersteuning internationale taal

Printerstatusbewaking

Ondersteuning geluid en licht herinnering functie

Ontwerp aan de voorkant voorkomt waterspatten

Geschikt voor keukentoepassingen

Specificatie:

Afdrukmethode	Direct thermisch
Karaktergrootte	ANK, FontA: 12 * 24dots, FontB: 9 * 17dots, Vereenvoudigd / Traditioneel Chinees: 24 * 24 dots
Kolomcapaciteit:	576dots / lijn OF 512dots / lijn
Codepagina	PC347 □Standard Europe□ □Katakana □ PC850 (meertalige), PC860 (Portugees), PC863 (Canadees-Frans), PC865 (Nordic), West-Europa □ Grieks □ Hebreeuws □ Oost-Europa □ Iran □ WPC1252 □ PC866 □Cyrillisch # 2□ □ PC852 □Latin2□ □ PC858 (Latin2) □ IranII □ Lets □ Arabisch □ PT151 □1251□
Barcode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / Code93 / CODE128
Afdruksnelheid	260mm / sec
Invoerbuffer	1024K bytes
Papier breedte	79,5 ± 0,5 mm
MCBF (levens)	100km
Opdracht afdrukken	Compatibel met ESC / POS
Kassaladecontrole	DC24V / 1A
Dikte papier	0.06-0.08mm
Snijder	Handmatige snijder
Rol papier	79,5 ± 0,5 mm * φ83 mm
Koppel	Serieel + USB + LAN

drivers	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / win 7 & 8 / Linux / win10
Stroomvoorziening	DC24V / 2.5A
Ingang voedingsadapter	AC 110V / 220V, 50 ~ 60Hz; uitgang □ DC 24V / 2.5A
Dimensie	185x140x134mm (L * B * H)
Gewicht	1,48 kg





OCPP-80M



Aocom
Thermal Receipt Printer
Model: OCPP-80M
Paper Width: 80mm
Print Speed: 260mm/s
Power Input: 24V --- 2.5A
Interface: RS232+USB+LAN
Command Support: ESC/POS
OCPP80M-NMBZ1908100030
CE FC CB RoHS
MADE IN CHINA





OCPP-80M





OCPP-80M

