

24 GHz draadloze laserbarcodescanner
(Model: OCBS -W600)

SPECIFICATIE:

FYSIEKE KENMERKEN	
Lichtbron:	Zichtbare laserdiode (VLD) @ 650 nm-670 nm
Scanner afmetingen:	164 mm * 67 mm * 95 mm(B * H * D)
Afmetingen ontvanger:	130 mm * 45 mm * 129 mm(B * H * D)
Materiaal:	ABS + TPR / aluminiumlegering
Gewicht:	235 g
Scanmodus:	Handbediend; bidirectionele scanmodus.
Indicatielampje:	LED rood en blauw
Zoemer:	Zoemervolume instelbaar
PRESTATIEKENMERKEN	
Breedte van scanveld:	60 mm bij 30 mm □ Van het motorgezicht □ 98 mm bij 100 mm □ van het motorgezicht □
Diepte van scanveld:	2,5 - 600 mm □ Contrast 0.9 Dichtheid 0.25 □
Scansnelheid:	100 scans / sec
Scan precisie:	0,10 mm □ 4mil □ PCS0.9
Bitfoutpercentage:	1 / (5 miljoen)
Decodeervermogen:	UPC / EAN, UPC / EAN met supplementen, UCC / EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS-varianten, Chinees 2 van 5
Accu:	3,7 V / 750 mAh, Li-ion
Oplaadtijd:	3.0 uur
Scan tijd:	30 uur
Actueel:	100mA (werkend); 40mA (standby)
Hoeken:	Hoogte: 60 °; Kantelen: 45 °
Communicatie afstand:	30m
Werkfrequentie:	2,4G
Geheugen	16 MB
Communicatie-interface:	USB
KENMERKEN VAN DE GEBRUIKERSOMGEVING	
Temperatuur:	0graad C tot 50graad C (Operationeel), -40graad C tot 70 graad C (Opslag)
Relatieve vochtigheid:	5% -90% (niet-condenserend)
Drop Specificatie:	Bestand tegen herhaalde vallen van 1,5 m op een betonnen ondergrond
Omgevingsverlichting:	0 ~ 100.000 LUX
Elektrostatische ontlading:	Conformeerd naar ±12KV luchtafvoer en ±6KV contactontlading
Veiligheidscertificaat:	CE, FCC, Klasse 2, RoHS

Productdetails:



Wireless Barcode Scanner

OCBS-W600



Product Picture





Features

Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100 scans/sec



Scan speed: 10000/second

Data transmission distance reaches 30m in open area;



Scan Time: 30hours



||| All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	2.5-600mm (Contrast 0.9 Density 0.25)
Scan Speed	100 scans/sec
Scan Precision	0.10mm (4mil) PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB ,RS232 ,PS2
USER ENVIRONMENT CHARACTERISTICS	
Temperature	0°C to 50°C (Operating), -40°C to 70°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.



Relevante documenten:

Wilt u meer productinformatie weten, klik dan hier.

[Specificatie](#)