

Thermische printer 80mm made in china (Model: OCPP-802)

Specificatie:

Drukmethode	Direct thermisch
Lettergrootte	ANK, FontA: 12 * 24dots, FontB: 9 * 17dots
Kolomcapaciteit	576dots / lijn of 512dots / lijn
Tekenset	PC347 (Standard Europa)Katakana, PC850(Meertalig)PC860(Portugees) PC863(Canadees-Frans)PC865(Nordic) West-Europa,Grieks,Hebreeuws,Oost-Europa,Iran,WPC1252,PC866(Cyrillisch # 2) PC852(Latin2)PC858,IranII,Lets,Arabisch,PT151(1251)
Barcode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / Code93 / CODE128
Afdruksnelheden	230mm / sec
Ontvang buffer	128k bytes
NV flash buffer	256K bytes
Papierbreedte	79,5 ± 0,5 mm
MCBF (leven)	100km
Afdrukken commando	Compatibel met ESC / POS
Kassalade controle	DC 12-24V / 1A
Papierdikte	0.06-0.08mm
Snijder	Handmatige Cutter
Papierrol	79,5 ± 0,5 mm * φ83mm
Interface	Serieel / parallel / USB / LAN
Bestuurder	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / win 7 / Linux
Stroomvoorziening	DC24V / 2.5A
Power adapter ingang	AC 110V / 220V, 50 ~ 60Hz; output:DC 24V / 2.5A
Dimensie	190x145x150mm
Gewicht	3.5kg

Details van het product:

