

# 15" white and black all in one touch windows restaurant pos computer

(M/N:POS-8619)

## Features:

Intel Celeron J1900 Quad core 2.0 GHZ

Hard Driver SSD 32GB (default),SSD 64GB and HDD320G for optional

5 wire resistive touch screen(default),Capacitive screen for optional

Card reader and VFD customer display for optional

## Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

## Parameter

|                           |                                       |
|---------------------------|---------------------------------------|
| Model                     | POS-8619                              |
| Color                     | Black and White                       |
| Optional Peripherals      | VFD220E                               |
| Main Board                | Intel Celeron Processor               |
| CPU                       | Intel Celeron J1900 Quad core 2.0 GHZ |
| Chipset                   | Intel NM70                            |
| Memory Support            | DDRIII 1066/1333*1 2GB (default)      |
| Hard Driver               | SSD 32GB (default)                    |
| LCD panel Size            | 15 inch TFT LCD                       |
| Brightness                | 350cd/m <sup>2</sup>                  |
| Resolution                | 1024*768(max)                         |
| Touch Screen              | 5 wire resistive touch screen         |
| View Angle                | Horizon: 150; Vertical :140           |
| I/O port                  | 1* power button 12V DC in jack*1      |
|                           | HDMI*1                                |
|                           | VGA(15Pin D-sub)*1                    |
|                           | LAN:RJ-45*1                           |
|                           | USB(2.0)*6                            |
|                           | RS232*1                               |
|                           | MIC IN*1 Audio out*1                  |
| Operating temperature     | 0°C to 40°C                           |
| Storage temperature       | -20°Cto 60°C                          |
| Compliance                | FCC Class A/CE Mark/LVD/CCC           |
| Packing dimension/ Weight | 410*310*410mm / 7.6 Kgs               |

|                  |  |
|------------------|--|
| Operating System | Windows XP above, Embedded, WEPOS, Linux         |
| Power adapter    | 110-240V/50-60HZ AC power, Input DC12/5A out put |

## Pictures

