

Ręczny skaner laserowy kodów kreskowych z podstawką

(Model: OCBS-LA06)

Cecha:

- 1.Auto-indukcyjny zbudowany w, zielony projektu;
- 2.High szybkość i dużą odległość odczytu skanowania;
- 3.Excellent dekodowania możliwości;
- 4.KBW, RS232 i USB obsługiwane;
- 5.Durable konstrukcja w połączeniu z ponadczasowymi rozwiązaniami;

Specyfikacja:

Charakterystyka wydajności	
Źródło światła:	Widoczne lasera (650-670nm)
Szybkość skanowania:	100 skanów na sekundę
Czytanie Odległość	2.5 ~ 600 mm (100% UPC / EAN)
Typ skanera:	Dwukierunkowy
Rozkład:	0,10 mm (4mil) w PCS 0,9
Drukuj Kontrast Minimalna:	20%, minimalna różnica odbiaskowe (@ 650nm)
Możliwość dekodowania:	UPC / EAN, UPC / EAN z supplementals, UCC / EAN128, kod 39, kod 39 pełne ASCII, kod 39 trioptic, kod 128, kod 128 full ASCII Codabar, Interleaved 2 of 5, dyskretny 2 z 5, Code 93, MSI, Code 11, ATA, warianty RSS, Chiński 2 z 5 ...
Charakterystyka fizyczna	
Obsługiwane interfejsy:	PS2, RS232, USB
Napięcie:	DC + 5V +/- 5%
Prąd:	100 mA
Prąd biegu jałowego:	& lt; 40 mA
Źródło prądu:	Host lub zewnętrznego zasilania (RS232) Zasilanie
Kąt skanowania	Nachylenia 45 ° Wysokość 60 °
Wymiary:	L165.42mm X W69.72mm X H89.67mm
Waga:	140g (bez podstawy)
Stoisko	Z
Kolor:	Kość słoniowa i czarny
Środowisko użytkownika	
Temperatura pracy:	0 °C ~ 50 °C
Temperatura przechowywania:	-40 °C ~ 70 °C
Wilgotność:	5 ~ 95% wilgotności względnej, bez kondensacji
Wyładowania elektrostatyczne:	Potwierdź do +/- absolutorium powietrza 15kV i +/- 8 kV z przy kontakcie
Rzuć Dane techniczne:	Wytrzymuje wielokrotne upadki na beton z 1.5m
Bezpieczny:	

EMI / RFI:	FCC Class A, CE
Bezpieczeństwo lasera:	Klasa lasera CDRH Produkt 2





Features

Simple but not easy

Auto-Induction built in, green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with
future-proofing



||| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product


Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



