

Mini usb laserowy czytnik kodów kreskowych (OCBS-LA11)

Funkcja:

- ✖ 1. Handheld laserowy kodów kreskowych skaner z funkcją automatycznego wykrywania;
- 2. Flexible współpracy z 360 stopni Obrót metalowa podstawka;
- 3. High szybkość skanowania (100 skanów / s) iduża odległość odczytu;
- 4. Excellent możliwość dekodowania;
- 5. KBW, RS232 i USB obsługiwane;
- 6. Grey i Czarny Kolor dostępny

Specyfikacja:

Wydajność Charakterystyka	
Lekki Źródło:	Widoczny laserowe (650-670nm)
Skanowanie Cena:	100 skanów na sekundę
Czytanie Dystans	2.5 ~ 600mm (100% UPC / EAN)
Typ skanera:	Dwukierunkowy
Rozdzielczość:	0,10 mm (4mil) w PCS 0,9
Drukuj Kontrast Minimalna:	30% minimum odbłaskowe Różnica (@ 650nm)
Error Rate:	1/3000000
Możliwość dekodowania:	UPC / EAN, UPC / EAN z supplementals, UCC / EAN128, kod 39, kod 39 pełne ASCII, kod 39 trioptic, kod 128, kod 128 full ASCII, Codabar, Interleaved 2 of 5, dyskretną 2 z 5, kod 93, MSI, Code 11, ATA, warianty RSS, chiński 2 z 5 ...
Fizyczne Charakterystyka	
Obsługiwane interfejsy:	PS2, RS232, USB
Napięcie:	DC + 5V +/- 5%
Prąd:	100 mA
Prąd biegu jałowego:	& lt; 40 mA
Źródło prądu:	Zewnętrzny zasilania lub Host (RS232) Zasilanie
Kąt skanowania	Nachylenie 45 ° Wysokość 60 °
Wymiary:	L165mm X W63mm X H87mm
Waga:	129g (bez podstawy)
Stań	Opcjonalne
Kolor:	Szary i czarny
Użytkownik Środowisko	
Operacyjny Temperatura:	0 °C ~ 40 °C
Przechowywanie Temperatura:	-40 °C ~ 60 °C
Wilgotność:	5 ~ 95% wilgotności względnej bez kondensacji
Elektrostatyczne Rozładować się:	Potwierdź +/- 15kV i wylotu powietrza +/- 8 kV wyładowania kontaktowego
Upuść Dane techniczne:	Wytrzymuje wielokrotne upadki na beton z 1.5m
Bezpieczny:	

EMI / RFI:	FCC Klasa A oraz CE
Bezpieczeństwo lasera:	CDRH klasy 2 Urządzenie laserowe



Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with
auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and
long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

