

Win CE na podstawie PDA przemysłowe

(Model: OCBS-D6000)

Specyfikacja:

System operacyjny		Okna CE 5.0 SDK dla wielu języków programowania, w tym C #, VB.net, VC ++, aby pomóc System developer
CPU		SAMSUNG S3C2451 533MHz
Pamięć		RAM DDR2 128MB, 256MB F-ROM
Wystawa		TFT-LED QVGA 2,8 calowy kolorowy ekran dotykowy LCD, rozdzielczość 240 * 320
Klawiatura		27 klawiszy
Komunikacja	Wifi (Domyślnie)	Wybudowany w 802 11b / g, funkcja komunikacji bezprzewodowej, stawka: 54MB / s, może spotkać CISCO Standard bezpieczeństwa CCX2,3
	GPRS (opcja)	Wsparcie GSM / GPRS 10, GSM27,10
Dane kolekcja (3 opcji)	1D skaner kodów kreskowych	Laserowy skaner kodów kreskowych, szybkość skanowania: 100 skanowanie / s Kod: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Książka ziemi EAN; Kod 128; UCC / EAN-128; Kod 39; Trioptic Code 39; Code 39 Full ASCII; Kod 93; Kod 11; Interleaved 2 z 5; Discrete 2 of 5; Pasek Coda; MSI; Bar GS1 danych 14; Ograniczona GS1 Data Bar; Dane GS1 Bar Expanded;
	2D Skaner kodów kreskowych	Kodów kreskowych 1D: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Książka ziemi EAN; Kod 128; UCC / EAN-128; Kod 39; Trioptic Code 39; Code 39 Full ASCII; Kod 93; Kod 11; Interleaved 2 z 5; Discrete 2 of 5; Pasek Coda; MSI; Dane Bar GS1 14; Ograniczona GS1 Data Bar; GS1 Data Bar Expanded; Kodów kreskowych 2D: PDF417, microPDF417, Kod Maxi, Maxi Code, Data Matrix, Composite Kody & amp; QR Code,
	RFID	13,56 MHz, ISO15693 wsparcia, ISO14443A / Umowa B
Moc	Bateria	3.7V 2600mAh
	Czekaj czas	120 godzin
	Działa czas	8 godzin
Rozszerzać port		Wsparcie Micro SD / TF do 16GB
Przemysłowy gatunek		IP65
Wymiary		169 (l) x 60 (W) x 31 (H) mm
Waga		320g (Obejmuje baterii)
Działa środowisko	Działać temperatura	-15 ~ + 50 Stopni C
	Sklep temperatura	-20 ~ + 60 Stopni C
	Działać wilgotność	595%
	Wilgotność Store	595%
	Wysokość Anti-sejsmiczne	1,2 m posadzka cementowa

Szczegóły Produktu:



ocom
All your side

Win CE based Industrial PDA

OCBS-D6000

Product Picture





Features

Simple but not easy

Default configuration :Wifi+1D barcode scanner;
Bluetooth, GPRS communication for option;
2D scanner, 125K/134.2K/13.56M Hz RFID
reader for options;





Win. CE 5.0 multi-language operation system;
Easy secondary development, compatible
with different software;

RAM DDR2 128MB, F-ROM 256MB;
High capacity 2800mA battery
and low consumption;



Industrial rugged design, water-proof
and protection grade(IP65);



and protection grade (IP 65),

All-round show





Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf



Parameter

Operation system	Windows CE 5.0, SDK for multiple programming languages including C#, VB.net, VC++ to assist system developer
CPU	SAMSUNG S3C2451 533MHZ
Memory	RAM DDR2 128MB, F-ROM 256MB
Display	TFT-LED QVGA 2.8 inch LCD color touch screen, resolution 240*320
Keyboard	27 keys
Wi-Fi (default)	Built in 802 11b/g wireless communication function, rate:

Communication		54MB/Sec, can meet CISCO CCX2,3 security standard
	GPRS(Optional)	Support GSM/GPRS 10,GSM27,10
Data collection (3 options)	1D barcode scanner	Laser Barcode scanner, Scan Rate: 100 scan/sec Code: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Book land EAN; Code 128; UCC/EAN-128; Code 39; Trioptic Code 39; Code 39 Full ASCII; Code 93; Code 11; Interleaved 2 of 5; Discrete 2 of 5; Coda bar; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Expanded;
	2D Barcode Scanner	1D barcode: UPC-A; UPC-E; UPC-E1; EAN-8; EAN-13; Book land EAN; Code 128; UCC/EAN-128; Code 39; Trioptic Code 39; Code 39 Full ASCII; Code 93; Code 11; Interleaved 2 of 5; Discrete 2 of 5; Coda bar; MSI; GS1 Data Bar 14; GS1 Data Bar Limited; GS1 Data Bar Expanded; 2D barcode: PDF417、microPDF417 ,Maxi Code, Maxi Code, Data Matrix, Composite Codes & QR Code,
	RFID	13.56MHZ, support ISO15693, ISO14443A/B agreement
Power	Battery	3.7V 2600MAH
	Standby time	120 hours
	Working time	8 hours
Expand port	Support Micro SD/TF card up to 16GB	
Industrial grade	IP65	
Dimensions	169(l)×60(W)×31(H) mm	
Weight	320g (include battery)	
Working environment	Operate temperature	-15~+50 Degree C
	Stock temperature	-20~+60 Degree C
	Operate humidity	5-95%
	Stock humidity	5-95%
	Height of Anti-seismic	1.2m cement floor

Production Line





Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Certifications



Packing and Shipment



Payment





Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?



Company Profile

This Assessed Supplier Has Been
Independently Verified

Build Your Growth On Trust



TÜV Rheinland





FORTUNE 500
Precisely Right.



OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.



OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,
Shenzhen 518054, China;

Websites: <http://www.thermalprinter.com.cn> ; <http://www.ocominc.com> ;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.



Odpowiednie dokumenty:

[*Specyfikacja](#)

[*D6000_OS_EN](#)

Powiązane Wideo:

FAQ: