

## Wysokiej jakości 433Mhz bezprzewodowy skaner kodów QR 2D Barcode z kołyski

**Model: OCBS-W231**

### Funkcje:

- 1, 433Mhz bezprzewodowej komunikacji odległość 300m odkryty, kryty 100m; Odległość do komunikacji bezprzewodowej Bluetooth odkryty 20m i 10m kryty;
- 2, wyposażony rezygnować komunikacji i ładująca
- 3, miękką plastikową osłonę do ochrony obiektywu i zarys znacznie zwiększa wydajność anty-drop;
- 4, kodów kreskowych na ekranie komputery i telefony komórkowe mogą być skanowane;
- 5, nie potrzeba kierowcy, plug & play;
- 6, może przechowywać więcej niż 10 000 sztuk danych;
- 7, wiele skanerów można podłączyć do jednego odbiornika (433mhz).

### Parametry:

Mające Źródło światła	617 nm LED
Źródła światła oświetlenie	625 nm LED
Kąt skanowania	39° (H) 25 ° (V)
Kąt obrotu	0 - 360°
Zmieniono kąt uniesienia działa	65 °
Kąt pochylenia	60 °
Kontrast wydruku	Wyższa niż 25%
1D	UPC/EAN, UPC/EAN z supplementals, BooklandEAN, ISSN, UCC kupon rozszerzone, za darmo Code128, GS1-128, ISBT 128, Code 39, kod 39 pełne ASCII, Trioptic Code 39, 32 kod, kod 93, Code11, Matrix 2 5, przeplatany 2 z 5, dyskretne 2of 5, Codabar, MSI, chiński 2, 5, Barvariants danych GS1, koreański 3 5, ISBT Concat
2D	Typu PDF417, MicroPDF417, złożonych kodów, TLC-39, DataMatrix, Maxicode, kod QR, MicroQR, Aztec
Interfejs	USB (kabel odbiornika Wireless)
Zasięg łączności	433mhz: wewnątrz: 100m; Na zewnątrz: 300m (maks.) Bluetooth: Wewnątrz: 10m; Zewnątrz: 20 m (maks.)
Temperatura pracy	-10 stopni C - 45 stopni C
Temperatura przechowywania	-20 stopni C - 65 stopni C
Wilgotność pracy	5-85%
Wilgotność podczas przechowywania	5% - 95%
Trwałość	Wytrzymuje wiele 1,5 m na beton
Moc wejściowa	5 v DC, 280mA
Czas ładowania	6h
Baterii	1500mAh
Jaskrawość	Wewnątrz: 3.000 LUX max; Zewnątrz światło słoneczne: max 86000 LUX
IP stopień	IP42
DEKODOWANIA ZAKRESÓW	

Typowa wydajność *		Typowe zakresy pracy	
		Zakres ostrości HD	
Typ kodu kreskowego	Gęstość symboli	W pobliżu	Znaczenie
Kod 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Kod 39	20,0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10,0 mil	5mm	110mm
Kod QR dla	20,0 mil	10mm	150mm
Rozdzielczość 1D kod 39	4 mil		
Rozdzielczość 2D Data Matrix	10 mil		
Materiał	ABS + PC		
Wymiar	Skaner (70 * 95 * 168 mm) Base(145*112*74mm)		
Waga netto	Skaner 185g Base 186g		
<b>Informacje o zamawianiu:</b>	<b>OCBS-W231-4:</b> bezprzewodowy skaner kodów kreskowych 2d 433mhz z podstawki		
	<b>OCBS-W231-B:</b> Bluetooth 2d barocde skaner z podstawki		



# FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

**1**

**FAST SCAN,HIGH RECOGNITION RATE**



**2**

**STRONG DECODING ABILITY**



**3**

**CRADLE FOR CHARGING AND WIRELESS COMMUNICATION**



**4**

**STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE**



**5**

**NO NEED DRIVER PLUG AND PLAY**



## THE PRODUCT FAMILY

---



## PRODUCT PACKAGING FIGURE

---





## WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



PRODUCT  
INORMATION

---

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),

Together we quest for the best.



## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

**Sales Center:**

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: [www.ocominc.com](http://www.ocominc.com) [www.possolution.com.cn](http://www.possolution.com.cn);

E-mail: [sales15@ocominc.com](mailto:sales15@ocominc.com)

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

*ocominc.com*

*ocominc*