

# OCPP-M05: android bluetooth 58mm drukarka termiczna, drukarka termiczna Kod QR

(Model: OCPP-M05)

## Cechy:

- 1.Support systemu Windows, Android,lub iOS, iOS lub Android + OS
- 2.Bluetooth, USB i RS232komunikacji dla opcji.
- 3.Higher szybkość druku 90 mm / s.
- 4,100 km TPH życia.
- 5.Low pobór mocyoraz duża pojemność baterii litowo.

## Specyfikacja:

|                            |                                                                                                                          |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Ogólna Wymiary (W x D x H) | 105 × 75 × 45 mm                                                                                                         |
| Waga                       | 134g                                                                                                                     |
| Kolor                      | Czarny                                                                                                                   |
| Efektywna szerokość druku  | 48mm                                                                                                                     |
| Metoda drukowania          | Drukowanie linii termiczny                                                                                               |
| Polecenia drukowania       | ESC / POS kompatybilny zestaw poleceń                                                                                    |
| Prędkość druku             | Do 90 mm / s                                                                                                             |
| Rozkład                    | 8 punktów / mm (203dpi)                                                                                                  |
| Czcionki Drukuj            | 12x24 / 24x24                                                                                                            |
| Pojemność kolumny          | 32 kolumn / 16columns                                                                                                    |
| Wielkość znaków            | 1,5 x 3,0 mm (szer x wys) / 3.0x3.0mm (SxW)                                                                              |
| Wymiary papieru            | 58,0 ± 0,1 mm x średnica 40.0mm                                                                                          |
| Grubość papieru            | Od 0,06 do 0,08 mm                                                                                                       |
| Zestaw znaków              | Alfanumeryczny / chiński Kanji                                                                                           |
| Berło                      | USB, RS-232, Bluetooth (opcja)                                                                                           |
| Migać                      | 256KB                                                                                                                    |
| Zasilacz                   | 9V DC / 2A                                                                                                               |
| Zasilanie bateryjne        | 7.4V DC / 1500mA; Akumulator może pozostać przez okres 4-5 dni, gdy jest pełna energii, może wydrukować 120-150m papieru |
| Inne funkcje               | Wykrywanie papieru, Detekcja zasilania, Instrukcja zamknięty                                                             |
| Warunki pracy              | Temperatura: -10 °C ~ 50 °C, Wilgotność: 10% ~ 90%                                                                       |
| Warunki przechowywania     | Temperatura: -20 °C ~ 70 °C, Wilgotność: 5% ~ 95%                                                                        |
| Nazwa urządzenia           | Można dostosować, List i cyfrowego dla opcji, w max 30 znaków ASCII.                                                     |
| Hasło                      | Wchodzić Domyślny kod parowania "1234", można go dostosować. Na max 6 Digitals.                                          |
| Wymiar wtyczka zasilania   | 3.5 * 1.1mm                                                                                                              |
|                            |                                                                                                                          |



## Bluetooth Thermal Printer OCP- M05



Picture





## Features

### Small Size, BIG Performance

Support Windows, Android, or IOS;




Higher print speed 90mm/sec;  
100km TPH Life;



Bluetooth, USB and RS232 communication for option;



Low power consumption and  
large capacity Lithium battery;





## All-round show



## Parameter

| Specifications            |                                                                                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------|
| Overall Dimension (W×D×H) | 105×75×45mm                                                                                           |
| Weight                    | 134g                                                                                                  |
| Color                     | Black                                                                                                 |
| Effective print width     | 48mm                                                                                                  |
| Print method              | Thermal line printing                                                                                 |
| Print commands            | ESC/POS compatible command set                                                                        |
| Print speed               | Up to 90mm/sec                                                                                        |
| Resolution                | 8 dots/mm(203dpi)                                                                                     |
| Print font                | 12x24/ 24x24                                                                                          |
| Column capacity           | 32 columns/ 16columns                                                                                 |
| Character size            | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)                                                                   |
| Paper dimensions          | 58.0±0.1mm x diameter 40.0mm                                                                          |
| Paper thickness           | 0.06 to 0.08mm                                                                                        |
| Character set             | Alphanumeric/ Chinese Kanji                                                                           |
| Interface                 | USB, RS-232 , Bluetooth(optional)                                                                     |
| Flash                     | 256KB                                                                                                 |
| Power Adapter             | 9V DC/2A                                                                                              |
| Battery Power             | 7.4V DC/ 1500mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features            | Paper detection, power detection, Manual shut down                                                    |

|                      |                                                                               |
|----------------------|-------------------------------------------------------------------------------|
| Working conditions   | Temperature:-10℃~50℃,Humidity:10%~90%                                         |
| Storage conditions   | Temperature:-20℃~70℃,Humidity:5%~95%                                          |
| Device name          | Can be customized, letter and digital for option, at max 30 ASCII characters. |
| Password             | Enter default pairing code "1234", it can be customized. At max 6 digitals.   |
| Power plug dimension | 3.5*1.1mm                                                                     |

## Applications

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Food Delivery



Restaurant



Bus / Taxi Receipt



Traffic Citation



Logistics



Transportation



Warehouse Management



Delivery



Illegal Parking Ticket




Drugstore



Price Tag



Retail / Farm





## Production Line



## Capacity

| Verified | Product Name                    | Production Line Capacity | Actual Units Produced(Previous Year) |
|----------|---------------------------------|--------------------------|--------------------------------------|
| ✓        | Thermal Printer                 | 40,000 Sets / Month      | 250,000 Sets                         |
| ✓        | Dot Matrix Printer              | 15,000 Sets / Month      | 10,000 Sets                          |
| ✓        | Bluetooth Printer               | 30,000 Sets / Month      | 20,000 Sets                          |
| ✓        | Barcode Scanner                 | 40,000 Sets / Month      | 20,000 Sets                          |
| ✓        | POS Machine                     | 5,000 Sets / Month       | 10,000 Sets                          |
| ✓        | Magnetic Card Reader and Writer | 45,000 Sets / Month      | 50,000 Sets                          |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

## Test Equipments

| Verified | Machine Name             | Brand & Model No. | Quantity |
|----------|--------------------------|-------------------|----------|
| ✓        | Ageing Tester            | No Information    | 6        |
| ✓        | Withstand Voltage Tester | CC2670A           | 1        |
| ✓        | Oscilloscope             | TBS1102           | 1        |
| ✓        | DC Power Supply          | PS-305DM          | 6        |
| ✓        | Digital Torque Meter     | HP100             | 1        |
| ✓        | Calliper                 | GUANGLU           | 2        |
| ✓        | Multi-meter              | VC890D            | 7        |
| ✓        | Test Computer            | No Information    | 13       |

✓ Indicates information has been verified onsite by TUV on 2013.7.15

## Certifications



## Packing and Shipment





## Payment



## Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





## Why you choose us?



Best Service

Authoritative Assessed

Flexible Cooperation

## Company Profile

**This Assessed Supplier Has Been  
Independently Verified**

Build Your Growth On Trust



**TÜVRheinland®**  
Precisely Right.



OCOM Technologies Limited, founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Europe, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.



## Contact us

**Any queries, please contact us immediately, big surprise is waiting for you.**

 Sales Center:

Address: 11/F, Tower A, New Energy Building, #2009, Nanhai Ave., Nanshan district, Shenzhen  
Guangdong, 518054, China;

E-mail: [ocom@ocominc.com](mailto:ocom@ocominc.com) , [ocomtech@gmail.com](mailto:ocomtech@gmail.com) ;

Skype: [ocominc2000](#), [ocominc](#);

MSN: [ocomtech@hotmail.com](mailto:ocomtech@hotmail.com), [ocominc@hotmail.com](mailto:ocominc@hotmail.com);

Trademanager: [szocominc](#), [cn1500439666](#);

QQ: 2485890637, 190852203;

Tel/Fax: +86.755.8605.3207.

