

Mini Portable 58mm Bluetooth Thermal Printer (Model Number: OCPP - M09)

This mini printer with model number OCPP -M09 is a Android (or IOS+ Android) ,Window, Linux, JAVA compatible battery powered 58mm portable mobile thermal pos printer which combines USB and Bluetooth (optional) communication ways together. This printer could be powered by bateria do ponownego ładowania, power adapter, or car charger (depending on specified models) . Special model can connect with 8 smart devices for printing at same time. We have CE, FCC and other required certifications.

Cechy:

- Mini size suitable for portable application;
- Windows, Java, Linux, Android (or Android +IOS) operation system supported;
- Bluetooth oraz USB communication supported;
- SDK for Android available;
- 1D, 2D barcode (QR code), and image printing supported;
- Can change the printer name, password, baud rate online;
- One printer can connected with up to 8 smart devices (7 Android, one Apple device) visa blue tooth;
- Low power consumption and large capacity Lithium battery (1500mAh), 4~5 days standby;
- Powered by bateria do ponownego ładowania, power adapter, or car charger (specified models)
- Higher print speed 70mm/sec;
- 100km thermal printer head life;
- Multiple languages supported;
- ESC/ POS command set compatible;

Specyfikacja:

Overall Dimension (WxDxH)	105x75x45mm
Waga	134g
Kolor	Czarny
Print method	Thermal line printing
Print commands	ESC/ POS compatible command set
Effective print width	48mm
Print speed	Up to 70mm/sec
Rezolucja	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	32 columns/ 16columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions	58.0±0.1mm x diameter 40.0mm
Paper thickness	0.06 to 0.08mm
Zestaw znaków	Alphanumeric/ Chinese Kanji
Berło	USB, Bluetooth (optional)
Błysk	256KB
Zasilacz	5V DC/2A
Moc baterii	7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Inne funkcje	Paper detection, manual shut down
Warunki pracy	Temperature:-10~50 degC, Humidity:10%~90%
Nazwa urządzenia	Can be customized, letter and digital for option, at max 30 ASCII characters.

Hasło	Enter default pairing code "1234", it can be customized or change by customer itself. At max 6 digitals.
Power plug dimension	3.5*1.1mm





OCPP-M09





OCP-PP-M09





OCP-PP-M09



