

Ocbs-L006 Dwukierunkowy USB ręczny laserowy skaner kodów kreskowych

(M / N: Ocbs-L006)

CECHA:

High szybkość skanowania i długa odległość odczytu;

doskonała dMożliwość ecode;

KBW, RS232 i USB obsługiwane;

Trwała konstrukcja w połączeniu z przyszłą-proofing;

SPECYFIKACJA:

| Charakterystyka wydajności | |
|-----------------------------------|---|
| Źródło światła: | Widoczne Laser (650-670nm) |
| Szybkość skanowania: | 100 skanów na sekundę |
| Odległość odczytu | 2,5 ~ 600mm (100% UPC / EAN) |
| Typ skanera: | Dwukierunkowy |
| Rozkład: | 0,10mm (4mil) przy PCS 0,9 |
| Drukuj Kontrast Minimalna: | 20%, minimalna różnica odbiaskowe (@ 650nm) |
| Możliwość dekodowania: | UPC / EAN, UPC / EAN w dodatkowy, UCC / EAN128, Code 39, Code 39 pełnej ASCII, Code 39 trioptic, kod 128, kod 128 full ASCII, bar coda, przeplatany 2 z 5, dyskretny 2 z 5, Code 93, MSI, Code 11, ATA, warianty RSS, Chinese 2 z 5 ... |
| Charakterystyka fizyczna | |
| Obsługiwane interfejsy: | PS2, RS232, USB |
| Napięcie: | DC + 5V +/- 5% |
| Aktualny: | 100 mA |
| Idle Current: | & Lt; 40 mA |
| Źródło prądu: | Host zasilania lub zewnętrznej (RS232) Zasilanie |
| Kąt skanowania | Nachylenia 45 ° Wysokość 60 ° |
| wymiary: | L165.42mm X W69.72mm X H89.67mm |
| Waga: | 140g (bez podstawy) |
| Stoisko | Zna zewnątrz |
| Kolor: | Ivory i czarny |
| Środowisko użytkownika | |
| Temperatura robocza: | 0 stopni C~ 50 stopni C |
| Temperatura przechowywania: | -40 stopni C~ 70 stopni C |
| Wilgotność: | 5 ~ 95% wilgotności względnej, bez kondensacji |
| Wyładowania elektrostatyczne: | Potwierdź do +/- Nawiew 15kV oraz +/- 8 kV wyładowania kontaktowego |
| Rozwijane Dane techniczne: | Wytrzymuje wielokrotne upadki na beton 1.5m |
| Bezpieczny: | |
| EMI / RFI: | FCC Class A, CE |
| Bezpieczeństwo lasera: | Klasa lasera CDRH Produkt 2 |



*Handheld Laser
Barcode Scanner*

OCBS-LA06



Product Picture





Features

Simple but not easy

Auto-Induction built in, green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with future-proofing



All-round show





Parameter

| Performance Characteristics | |
|-----------------------------|--|
| Light Source: | Visible laser (650-670nm) |
| Scan Rate: | 100 scans per second |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Scanner Type: | Bi-directional |
| Resolution: | 0.10mm (4mil) at PCS 0.9 |
| Print Contrast Minimum: | 20%, minimum reflective difference (@650nm) |
| Decode Capability: | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| Physical Characteristics | |

| | |
|--------------------------|--|
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | DC+5V+/-5% |
| Current: | 100 mA |
| Idle Current: | <40 mA |
| Power Source: | Host power or external (RS232) power supply |
| Scanning Angle | Inclination 45° Elevation 60° |
| Dimensions: | L165.42mm X W69.72mm X H89.67mm |
| Weight: | 140g (without stand) |
| Stand | With |
| Color: | Ivory and black |
| User Environment | |
| Operating Temperature: | 0°C~50°C |
| Storage Temperature: | -40°C~70°C |
| Humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic Discharge: | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete |
| Safe: | |
| EMI/RFI: | FCC Class A and CE |
| Laser Safety: | CDRH class 2 laser product |


Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

