

21.5 Inch Windows/Android Self-Service POS System

(M/N: POS -K003)

Cechy:

Top design in this kiosk industry, quick responses, run stably;

Highly integrating multi-function, space-saving, easy to operate;

Best shopping experience and improving the store image;

Labor cost-saving;

Time saving for the customers waiting at cashier front desk;

High quality scanner make goods-scanning quickly;

Support the payment of Wechat and Alipay;

Support wall-mounting and standing alone.

Specifikation

Model	POS -K003-W	POS -K003-A
Imię	21.5 inch all in one touch screen Kiosk	
Mieszkania	plastic with metal combined	
Kolor	whole white kolor	
Wyświetlacz		
Main screen size	21.5 inch touch screen monitor	21.5 inch touch screen monitor
Rezolucja	1920*1080	1920*1080
kolorJasność	250cd/m2	
View angle	Horyzont: 178; Pionowy :178	
Dotykać screen	10-punkt projected G+G capacitive touch	
Występ		
Płyta główna	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4th generation CPU for option	ARM Cortex-A17 -RK 3288 quad core 1.8GHz CPU
System Pamięć	1*SO-DIMM DDRIII slot, support1333*/1600 4GB	On board 2GB DDRIII
Urządzenie pamięci masowej	M SATA SSD 64GB	16.GB eMMC
Audio	On board Real Tek ALC662 audio chip	On board Real Tek audio chip ALC5640
LAN	10/100Mbs, Realtek RTL8111F Lan chip	10M/100M, RTL8201F
WIFI	Support 802.11 a/b/g	Support 802.11 a/b/g
Głośnik	Built in 8ohm/10watt speakers	
Kamera	Face recognition for payment (option)	
System operacyjny	Windows.7/8/10, Embedded, WE POS ,Linux	Android 7.1.
Connectivity		
External I/O port (J1900/RK3288)	Power przełącznik* 1.	
	100V-240V 50HZ/60HZ AC power Socket* 1.	
	USB*2	
	LAN:RJ-45*1	
Scanning platform	pakiet	
Źródło światła	Illumination:617nm red LED	
Zasilacz	5V DC	
Support 1D	UPC,EAN, Code128, Code 39,Code 93, Kod11., Interleaved 2 of 5, Matrix 2 of 5, Codabar, MSI Plessey,GS1 DataBar,China Pos tal,Korean Pos tal, etc....	
Support 2D	PDF417, Micro PDF417, Data Matrix, Maxicode, QR Code, Micro QR, Aztec, Hanxin, etc.....	

Barcode precision	4 mil code39
Barcode Sensitivity	Poziom: $\pm 60^\circ$ @ 0° Roll and 0° Skew Rolka: $\pm 360^\circ$ @ 0° Pitch and 0° Krzywy Krzywy: $\pm 65^\circ$ @ 0° Roll and 0° Poziom
Prompt Mode	Brzęczyk
Berło	USB
Drukarka	
80mm thermal printer	Direct thermal printing
	1.5.0mm/s printing speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	Automatyczny cutter function
	Power DC 24V
	Resoluiton 203DPI
Środowisko	
Temperatura robocza	0. to 40 stopni Celsjusza
Temperatura przechowywania	-10 to 60 stopni Celsjusza
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Akcesoria	
Przewód zasilający	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside (Opcja)
Inny	
Zgodność	FCC Class A/CE Mark/LVD/CCC



POS-K003





POS-K003





POS-K003







POS-K003



