

Supermarket Desktop USB - wielokierunkowy skaner kodów kreskowych

(OCBS-T008)

Desktop Omni-directional Barcode Scanner

20 linii skanowania w pięciu kierunkach

Konstrukcja zasilania NICAM, odpowiednia do hałaśliwego otoczenia

Wygląd to zwięzła i łatwa, stabilna wydajność, zgodna z wszelkiego rodzaju środowiskami biznesowymi

Możliwość skanowania wielu / pojedynczych linii, spełniają różne wymagania

Wiele interfejsów: PS / 2, RS232 lub USB

Obsługuje funkcję automatycznego budzenia

Niebieskie światła LED, głośne sygnały brzęczyka

Specyfikacja:

Parametry wydajności	
Zródło światła	Widoczny laser diodowy o długości fali 650 nm
Interfejs systemu	KBW, RS232, USB
Parametry fizyczne	
Objętość (dł. X szer. X wys.)	Bez podstawy: 140 mm * 83 mm * 75 mm Ze stojakiem: 157 mm * 98,3 mm * 100 mm
Waga	Waga netto (282 g); z podstawą (379 g)
Stoisko	Naprawiono podstawkę instalacyjną
Kolor	czarny
Parametry elektryczne	
Napięcie wejściowe	5,0 VDC +/- 10%
Prąd znamionowy	275mA
Moc	2W
Klasa lasera	CDRH klasa IIa; IEC 60825-1: Klasa I
Parametr środowiskowy	
temperatura robocza	0 ° C - 40 ° C
Temperatura przechowywania	-40 ° C - 70 ° C
Wilgotność	5% do 95% wilgotności względnej (bez kondensacji)
Charakterystyka Antiknocka	Aby wytrzymać upadek z wysokości 1,2 metra.
Odporność na światło	oświetlenie wewnętrzne, światło słoneczne, fluorescencja, światło żarowe, światło rtęciowe, światło pary sodowej: 450 Ft Świece (4844 Lux) światło dzienne: 8000Ft Świece (86111 Lux)
Parametry skanowania	
Tryb skanowania	Omni kierunkowa 20 linii, 5 kierunków, 20 linii skanowania
Szybkość skanowania	1500 razy na sekundę
Kąt skanowania	0 ~ 360 stopni (wielokierunkowe)
Odchylenie skanowania	+/- 50 stopni

Kontrast drukowania	Minimum 25% różnicy odbicia
Głębokość skanowania pliku	0 ~ 216 mm przy 13 mm (100% UPC / EAN)
Znamionowy zakres roboczy	5 mil: (38%) 10 ~ 64 mm 7,8 mil: (60%) 0 ~ 152 mm 10,4 mil: (80%) 0 ~ 190 mm 13 mil: (100%) 0 ~ 216 mm
Najniższa rozdzielczość	5 mil
Zdolność dekodowania	UPC / EAN / JAN, UCC / EAN 128, Code128, Code 39, Code 39 Trioptic, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code 93, Code 11, Code bar, MSI etc.



OCBS-T008





OCBS-T008





OCBS-T008



Production Line



Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets

✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6

✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ Indicates information has been verified onsite by TUV on 2013.7.15

Certifications



Packing and Shipment



Double wall corrugated board



Double outer cartons

Marks and fragile stickers



Outer protection film





Payment



Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





Why you choose us?

