

11.6 inch android cheap touch screen all in one pc

(POS-B11.6)

Features:

all in one,all in one pc,cheap all in one pc,cheap touch screen all in one pc

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system

2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

2GB RAM+8GB ROM standard (Android)

2GB RAM+32GB SSD standard (Windows)

11.6 inch Multi-point capacitive touch screen

Embedded 58mm or 80mm thermal printer(Optional)

Embedded MSR RFID reader(Optional)

Stylish display panel

Applications:

all in one,all in one pc,cheap all in one pc,cheap touch screen all in one pc

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter:

Model	POS-B11.6/POS-B11.6-A
Main Board①	Intel Celeron Processor J1900 Quad core 2.0GHz (Windows)
Main Board②	2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android)
OS①	Windows7(Beta)
OS②	Android 5.1
Memory①	2GB RAM 32GB SSD (Windows)
Memory②	2GB RAM 8GB ROM (Android)
Touch Screen	Multi-point capacitive touch
Screen Size	Main screen12 inch,Vice screen 12 inch
Color	Black or White
Printer	58mm big gear thermal printer or 80mm thermal printer with Auto cutter(Optional)
I/O port①J1900	USB*4 RJ45*1 RJ11*1[optional] VGA*1 HDMI*1(for vice screen) DB9 RS232 port *1,(can add 2 ports for optional)
I/O port②A83T	RJ11*1 (Opional) TF slot *1 RJ45*1 HDMI*1(for vice screen) USB*2 (can add 4 ports for optional) DB9 RS232 port*1 Audio*1 USB OTG port*1
Operating temperature	0°C to 40°C
Other Function (Android)	Bluetooth, WIFI
Optional items(Windows)	LCD VFD display,RFID,MSR camera,3G, DB25 parallel port, DB9 RS232 port*3 Other size Screen
Optional items(Android)	3G,4G camera, LCD VFD display,RFID,MSR,Other size Screen
Storage temperature	-20°Cto 60°C

Packing dimension	46*43*51cm
Power adapter	110-240V/50-60HZ AC power Input, 12/24V output depending on the printer



