

15 Inch All-in-one Touch Screen POS Machine in China (POS8829)

Features:

15 Inch All-in-one Touch Screen POS Machine in China
 15 Inch All-in-one Touch Screen POS Machine
 Fashion wine red appearance beautiful and streamlined design
 Humanized design can desktop or wall-mounted
 Inter processor 1037U dual core 1.8GHz
 1024x768 high resolution
 Magnetic card reader, LCD customer display, LED8 display, wifi optional
 SATA2.5 320GB or 500GB or SSD32GB
 15 inch TFT LCD and 5 wire resistive touch screen
 PS/2x2, serial3 DB9 malex3, parallel USB2.0x6, Parallel DB25 port, VGA, LAN port;
 HDMI, RJ11 for cash drawer optional

Applications:

- | Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
- | Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
- | Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket
- | Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Specifications:

Model	POS8829
Optional Color	Black/ Wine red
Optional Peripherals	ISO Track1/2/3 Magnetic Stripe Reader; LCD Customer display; LED8; WIFI
Main Board	Intel Chipset
CPU	1037U dual core 1.8G
Chipset	1037U + ICH8 Chipset
Memory Support	DDRIII 1066/1333*1 2GB(up to 4GB)
Hard Driver	SATA 2.5 320GB or 500GB or SSD32GB
LCD panel Size	15 inch TFT LCD
Brightness	350cd/m ²
Resolution	1024*768(max)
Touch Screen	5 wire resistive touch screen
View Angle	Horizon: 150; Vertical: 140
I/O port	1* power button
	PS2 mouse*1; PS2 keyboard*1
	Serial*3 DB9 male
	Parallel * 1, DB25 Parallel port
	VGA(15Pin D-sub)*1
	LAN: RJ-45*1 HDMI * 1 RJ*11 for cash drawer optional
	USB(2.0) * 6
	Audio out*12*Internal Speaker(option), MIC IN*1

Operating temperature	0 to 40 degree centigrade
Storage temperature	-20 to 60 degree centigrade
Power Consumption	35W(max)
Compliance	FCC Class A/CE Mark/LVD/CCC
Packing dimension/ Weight	440*270*425mm / 8 KGS
Operating System	Windows XP Professional Embedded (WEPOS, Linux compatible)
Power adapter	110-240V/50-60HZ AC power Input, DC12/5A output