

15 inch touch screen POS terminal machine all in one built-in thermal printer

(M/N:POS-C15/C12)



Keywords:

POS terminal,POS machine,POS all in one

Features:

l Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system

l 2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

l 2GB RAM+8GB ROM standard (Android)

l 2GB RAM+32GB SSD standard (Windows)

l 12/15 inches main capacitive touch screen

l Built-in 58/80mm big gear thermal printer for options

l Magnetic member card reader for optional

l VFD customer display or vice screen

Applications:

l Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

l Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

l Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

l Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter

| | |
|-------|--|
| Model | POS-C15/C12 |
| Color | Silver-gray, white or Black |
| CPU□ | Intel Celeron J1900 Quad core 2.0 GHZ |
| CPU□ | 2.0GHz A83T ARM 8-Core Cortex-A7 Processor |

| | | |
|-------------------------|--|-------------------|
| Memory□ | DDRIII 1066/1333*1 2GB (default) (Windows) | |
| Memory□ | 2GB RAM 8GB ROM □Android□ | |
| OS□ | Windows7(Beta) | |
| OS□ | Android 5.1 | |
| Hard Driver | SSD 32GB (default) (Windows) | |
| LCD panel Size | 15 inch TFT LCD | |
| Brightness | 350cd/m2 | |
| Resolution | 1024*768(max) | |
| Touch Screen | Capacitive touch screen | |
| Printer Parameter | Print Density | 203dpi |
| | Printing Command | ESC/POS |
| | Paper Roll Diameter | 60mm |
| | Paper Width | 58mm or 80mm |
| | Printing Speed | 60mm/s or 150mm/s |
| | MCBF(life) | 50km |
| Other optional function | MSR/ VFD220 customer display/ vice screen | |
| View Angle | Horizon: 150; Vertical :140 | |
| I/O port□J1900□ | 1* power button 12V DC in jack*1 | |
| | HDMI*1 | |
| | VGA(15Pin D-sub)*1 | |
| | LAN:RJ-45*1 | |
| | USB(2.0)*4 | |
| | RS232*2 | |
| | MIC IN*1 Audio out*1 | |
| I/O port□A83T□ | RJ11*1 (Optional) | |
| | TF slot *1 | |
| | RJ45*1 | |
| | HDMI for vice screen | |
| | DB9 RS232 port*1□USB*2 | |
| | Audio*1 | |
| Operating temperature | 0°C to 40°C | |
| Storage temperature | -20°Cto 60°C | |
| Operating System | Windows XP above, Embedded,WEPOS,Linux | |
| Power adapter | 110-240V/50-60HZ AC power, Input DC12/5A out put | |