15.6" All in One payment terminal Restaurant Ordering Machine pos system

(Model No.: POS-15T01-W/A)

Features:

Stylish and simple design;

15.6 inch 1366*768 resolution ultra-thin screen;

360 degree screen rotation angle;

Support Windows or Android system;

Ten-point capacitive touch screen;

Support for optional 15.6-inch or 11.6-inch secondary screen;

MSR, Customer display for option;

Modular design for easy assembly, disassembly, replacement and repair.

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

Specifications:

| Model | POS-15T01-W/A (W for Windows, A for Android) |
|------------------|---|
| Main board ① | Quad core 1.99 GHz J1900N for Windows version |
| Main board ② | Quad core 1.8GHz RK3288 for Android version |
| Windows OS | Windows 7 Ultimate demo version without license |
| Android OS | Android 6.0 |
| Windows RAM | 2GB Standard 4GB 8GB for option |
| Android RAM | 2GB |
| Windows Memory | 32GB SSD standard,64GB,128GB for option |
| Android Memory | 8GB eMMC, support 32GB TF card Expand |
| Screen Size | 15.6 inch Main Screen |
| Secondary screen | 15.6 inch or 11.6 inch |
| Customer Display | VFD or LCD |
| Resolution | 1366*768 |
| | |

| Touch Screen | ten-point capacitive touch screen |
|-----------------------|---|
| Brightness | 350cd/m ² |
| View Angle | Horizon: 150; Vertical: 140 |
| J1900 I/O port | VGA*1, USB*5, RS232*1, DC input*1 RJ45(Ethernet port)*1, Audio output*1 |
| RK3288 I/O Port | USB*5, RS232*2, DC input*1, RJ11□Cash drawer port□*1 RJ45(Ethernet port)*1, Audio output*1, MIC*1 |
| Operating temperature | 0 to 40 degree centigrade |
| Storage temperature | -20 to 60 degree centigrade |
| Power adapter | 110-240V/50-60HZ AC power Input, DC12/5A output |

















POS-15T01







POS-15T01

