

# 15.6" Capacitive Touch Screen Vfd Display POS System for Lottery

## (Model No.: POS-15T01-W/A)

### Features:

Stylish and simple design;

15.6 inch 1366\*768 resolution ultra-thin screen;

360 degree screen rotation angle;

Support Windows or Android system;

Ten-point capacitive touch screen;

Support for optional 15.6-inch or 11.6-inch secondary screen;

MSR, Customer display for option;

Modular design for easy assembly, disassembly, replacement and repair.

### Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop;

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop;

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket;

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf.

### Specifications:

|                  |   |
|------------------|---|
| Model            | POS-15T01-W/A (W for Windows, A for Android)    |
| Main board ①     | Quad core 1.99 GHz J1900N for Windows version   |
| Main board ②     | Quad core 1.8GHz RK3288 for Android version     |
| Windows OS       | Windows 7 Ultimate demo version without license |
| Android OS       | Android 6.0                                     |
| Windows RAM      | 2GB Standard 4GB 8GB for option                 |
| Android RAM      | 2GB   |
| Windows Memory   | 32GB SSD standard, 64GB, 128GB for option       |
| Android Memory   | 8GB eMMC, support 32GB TF card Expand           |
| Screen Size      | 15.6 inch Main Screen                           |
| Secondary screen | 15.6 inch or 11.6 inch                          |
| Customer Display | VFD or LCD                                      |
| Resolution       | 1366*768  |
| Touch Screen     | ten-point capacitive touch screen               |

|                       |  |
|-----------------------|--|
| Brightness            | 350cd/m <sup>2</sup>   |
| View Angle            | Horizon: 150; Vertical: 140  |
| J1900 I/O port        | VGA*1, USB*5, RS232*1, DC input*1<br>RJ45(Ethernet port)*1, Audio output*1                           |
| RK3288 I/O Port       | USB*5, RS232*2, DC input*1, RJ11□Cash drawer port□*1<br>RJ45(Ethernet port)*1, Audio output*1, MIC*1 |
| Operating temperature | 0 to 40 degree centigrade  |
| Storage temperature   | -20 to 60 degree centigrade  |
| Power adapter         | 110-240V/50-60HZ AC power Input, DC12/5A output  |











POS-15T01







POS-15T01





POS-15T01







