

## 15.6 inch hotel point of sale capacitive all in one cash register

(Model: POS -15T01-W / A)



### **feature:**

Sleek minimalist design

15.6" 1366 \* 768 resolution slim screen

360 degree screen rotation angle

Support for Windows or Android systems

Ten-point capacitive touch screen

Optional secondary screen 15.6 inches or 11.6 inches

MSR, customer display options

Modular design, easy to assemble, disassemble, replace and repair

application:

Dining: hotels, restaurants, fast food restaurants, coffee shops, bakeries and cake shops

Retailers: commercial streets, boutiques, department stores, cosmetics stores and premium barbershops

Entertainment: sauna, spa, night club, theme park, casino and lottery point of sale

Business: information management terminal for parking lots, hotels, airlines, subways, stations and terminals

**Product specifications:**

|                          |   |
|--------------------------|---|
| model                    | POS -15T01-W / A (W for Windows, A for Android)   |
| Motherboard 1            | Quad-core 1.99 GHz J1900N for Windows version   |
| Motherboard 2            | Quad-core 1.8GHz RK3288 for Android   |
| Windows operating system | Windows 7 Ultimate demo without license   |
| Android operating system | Android 6.0   |
| Windows RAM              | 4GB standard 8GB or higher optional   |
| Android RAM              | 2GB   |
| Windows memory           | 64GB SSD standard, , 128GB or higher optional   |
| Android memory           | 8GB eMMC, support 32GB TF card expansion  |
| screen size              | 15.6-inch home screen   |
| Auxiliary screen         | 15.6 inches or 11.6 inches  |
| Customer show            | VFD or LCD  |
| Resolution               | 1366 * 768  |
| touch screen             | Ten-point capacitive touch screen   |
| brightness               | Brightness 350cd / meter <sup>2</sup>   |
| Perspective              | Horizon: 150; vertical: 140   |
| J1900 I / O port         | VGA * 1, USB * 5, RS232 * 1, DC input * 1<br>RJ45 (Ethernet port)* 1, audio output* 1                                 |
| RK3288 I / O port        | USB * 5, RS232 * 2, DC input * 1, RJ11 (cash drawer port) *<br>1<br>RJ45 (Ethernet port)* 1, audio output* 1, MIC * 1 |
| Operating temperature    | 0 to 40 degrees Celsius   |
| Storage temperature      | -20 to 60 degrees Celsius   |
| Power Adapter            | 110-240V / 50-60HZ AC power input, DC12 / 5A output   |

**image:**





POS-15T01





POS-15T01





POS-15T01





POS-15T01







POS-15T01



**Involvedd PRODUCTS:**

<https://www.ocominc.com/products/All-in-one-POS-Machine.htm>