

## 15.6 or 15.1 Inch All In One Touch POS Terminal

(M/N:POS-G156/G151)

OCOM G series pos integrated high speed thermal printer inside,R&D team take time study and research to choose each materials carefully to ensure the machine work more stably and reliably,rich IO interface make a lot of connectivities available,fashionable appearance and easily maintain and flexibly be upgraded by customers.it is the best choice for many application sites such as restaurants, coffee shops,retail stores etc...

### Features:

- \*Intel Celeron series and intel core I3 I5 processor for optional
- \*Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for optional
- \*58mm and 80mm high speed thermal printer built in for optional
- \*Multi-point projected capacitive touch panel
- \*Optional side MSR and VFD220 customer display mounted to back cover
- \*Ture flat and water-proof scratch-resistant surface display

### Specification

Model	POS-G156	POS-G151
Name	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Housing	plastic with metal combined	
Color	whole pearl white machine body or pearl white match gray machine body	
Display		
Main screen	15.6 inch touch screen monitor	15.1 inch touch screen monitor
Resolution	1366*768	1024*768
Brightness	250cd/m <sup>2</sup>	
View angle	Horizon: 160; Vertical :150	
Touch screen	Multi-point projected G+G capacitive touch	
Sub-display	15.6inch display and 13.3 inch display W or W/o touch function, resolution 1366*768 for optional	15.1inch display W or W/o touch function, resolution 1024*768
Customer display	2*20 VFD mounted to back cover for optional	
Performance		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 <sup>th</sup> generation CPU for optional	
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 4GB (default) 2GB/8GB for optional	
Storage device	Msata SSD 64GB or higer, up to 256GB	
Audio	On board Real Tek ALC662 audio chip	

Speaker	8Ohm/5W speaker inside for optional
LAN	10/100Mbps,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
Connectivity	
External I/O port(J1900)	power button*1
	12V DC in jack*1
	LPT *1
	COM(RS232) * 1
	VGA(15Pin D-sub)*1
	LAN:RJ-45*1
	RJ11 for Cash drawer *1
	USB 3.0*1,USB2.0*4
	PS/2 *1 for mouse and keyboard
	MIC in*1 Audio out*1
Options	
80mm thermal printer	direct thermal printing
	150mm/s printing speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with auto cutter function and thermal head life 100km
	USB communication
58mm thermal printer	direct thermal printing
	80mm/s printing speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
	LPT communication
MSR	optional side MSR
Web camera	web camera mounted on top of the display for optional
Package	package
Weight	Net 6.5Kg Gross 8.5Kg for 15.6 dual screen
Package with foam inside	300*465*500mm
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%
Accessories	
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A output adaptor only for W/80mm printer machine
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Motherboard driver and touch driver inside
Other	
Compliance	FCC Class A/CE Mark/LVD/CCC

More product pictures shown



Easily loading thermal paper without tools



cable management, open and close the back cover



Conveniently access the machine via side USB port for uploading or downloading



## External I/O ports



## Package

