

# 15.6 Inch All In One Touch POS Terminal

(M/N:POS-L156)

OCOM POS-L156 series pos integrated high speed thermal printer inside,stylish design,working stably and reliably,rich IO interface make a lot of connectivities available,easily maintain and flexibly be upgraded by customers.it is the best choice for many application sites such as restaurants, coffee shops,retail stores etc...

## Features:

- l. Intel Celeron series and intel core I3 I5 processor for option
- m. Hard Driver Msata SSD 64GB ,SSD 128GB and 256 GB for option
- n. 58mm and 80mm high speed thermal printer built in for option
- o. Multi-point projected capacitive touch panel
- p. Optional side MSR and VFD220 customer display mounted to back cover
- q. True flat and water-proof scratch-resistant surface display

## Specification

Model	POS-L156
Name	15.6 inch all in one touch screen pos terminal
Housing	plastic with metal combined
Color	whole white machine body or whole black machine body
<b>Display</b>	
Main screen	15.6 inch touch screen monitor
Resolution	1366*768
Brightness	250cd/m <sup>2</sup>
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	15.6inch display W/ or W/o touch function, resolution 1366*768 for option
Customer display	2*20 VFD mounted to back cover for option
<b>Performance</b>	
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz ,or intel celeron J4125,or intel core I3 / I5 CPU for option
System Memory	1*SO-DIMM DDR3L slot, support 4GB DDR3L/1333MHZ(default) ,8GB for option
Storage device	Msata SSD 64GB or higher, up to 256GB
Audio	On board Real Tek ALC662 audio chip
LAN	10/100Mbps,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module
Operating System	Windows7/8/10, Embedded,WEPOS,Linux
<b>Connectivity</b>	

External I/O port J1900	power button*1
	12V DC in Jack*1
	LAN:RJ-45*1,RJ11 for cash drawer
	USB*6
	15PIN D-sub VGA *1
	RS 232*1
	line out*1,MIC in*1
<b>Options</b>	
80mm thermal printer	direct thermal printing
	150mm/s printing speed
	79.5-/+ 0.5mm paper width and printable width 72mm
	with auto cutter function and thermal head life 50km
58mm thermal printer	direct thermal printing
	85mm/s printing speed
	57.5-/+ 0.5mm paper width and printable width 48mm
	thermal head life 50km
MSR	optional side MSR
Web camera	web camera mounted on top of the display for option
Scanner	support 1D&2D code-scanning for option
Speaker	4ohm/5w speakers inside for option
<b>Package</b>	
Weight	Net□6.5Kg , Gross:8.0Kg for 15.6 with 15.6 dual screen with printer built in
Package with foam inside	490*310*485mm
<b>Accessories</b>	
Power adapter	200-240V/50-60HZ(default),110-240V/50-60HZ AC power input ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine 200-240V/50-60HZ(default),110-240V/50-60HZ DC12V/8A output adaptor only for W/ 80mm printer machine
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available













